

Rm.1804, Wensheng Center, Wenjin Plaza, 1010 Wenjin Road (N), Shenzhen 518020, China
Tel: +86 755 2563 1576, 2563 1639 Fax: +86 755 2560 0566, 2562 5060
E-mail: info@chinary.com.cn
[Http: //www.chinary.com.cn](http://www.chinary.com.cn)

Specifications		Thickness (mm)										
		0.4-0.58	0.58-0.79	0.79-0.99	0.99-1.19	1.19-1.50	1.50-1.98	1.98-3.05	3.05-4.06	4.06-5.59	5.59-6.86	6.86-9.40
O.D. (mm)	6.35-12.70	✓	✓	✓	✓	✓	✓					
	12.70-19.05	✓	✓	✓	✓	✓	✓	✓	✓			
	19.05-25.40	✓	✓	✓	✓	✓	✓	✓	✓			
	25.40-34.93		✓	✓	✓	✓	✓	✓	✓	✓		
	34.93-38.10		✓	✓	✓	✓	✓	✓	✓	✓		
	38.10-49.53			✓	✓	✓	✓	✓	✓	✓	✓	
	49.53-63.50			✓	✓	✓	✓	✓	✓	✓	✓	✓
	63.50-69.85				✓	✓	✓	✓	✓	✓	✓	✓
	69.85-85.73				✓	✓	✓	✓	✓	✓	✓	✓
	85.73-101.60					✓	✓	✓	✓	✓	✓	✓
	101.60-136.53						✓	✓	✓	✓		
	136.53-158.75											
	158.75-219.08											
Remarks		◎ Tubes with marks ✓ are supplied ◎ Standard: ASTM B280(GB/T17791-2007), ASTM B88 ◎ Materials:C11000(T2), C12200(TP2) ◎ Outer diameter: 6.35 to 219mm ◎ Thickness: 0.4 to 9.4mm ◎ Length: 1 to 10m ◎ If you will have any special requirements about specifications, please contact us so as to meet the demands										
Packing		in capped each tube trapped and in fumigated wooden cases, or as the customer's requests										