Model 6660 Mini Bus









外形参数 Size

总长/总宽/总高(mm) Overall Dimension (Length/Width/Heigh, mm)

发动机 Engine

I发动机型号 Engine model	依维柯索菲姆欧二排放柴油机SOFIM 8140.43
	IVECO SOFIM diesel engine SOFIM 8140.43 (Euro 2 emission)
发动机型式 Engine type	前置,直列四缸四冲程、增压中冷、水冷
	Front mounted, 4 cylinders in-line, 4 stroke, turbo-charged, water cooled
最大功率/转速	87/3600
Max.power/rotating speed (kw/rpm)	
最大扭矩/转速	269/1900
Max. torque/rotating speed (N.m/rpm)	

性能参数 Performance

底盘型号 Chassis model	EQ6570K3AC
最高车速 Top speed (km/h)	85
油耗(L/100km)(限定工况下)	≤16
Fuel consumption (on certain condition)	
油箱容量(L)	90
Fuel tank capacity (L)	

基本配置 Basic Specification	
离合器 Clutch	单片、干式、φ267,液压传动气助力
	Single, dry, φ267, hydraulic air booster
变速器 Transmission	依维柯5档手动 IVECO 5 forward gears, manual
后桥 Rear axle	单级减速,整体式桥壳
	Integral axle housing, single reduction final drive
前桥 Front axle	拳端式工字梁结构 ends fist, I section
悬架系统 Suspension system	钢板弹簧,9/8 Leaf spring, 9/8
转向系统 Steering system	国产整体式动力转向 Domestic integral power steering
制动系统 Braking system	双管路液压制动,中央鼓式驻车制动
	Dual-circuit hydraulic brake, central drum parking brake
轮胎 Tire	7.00-16
功能配置 Functional Specification	
车身 Body	客车车身骨架和底架主要由矩型钢管经磷化浸漆后组焊而成,车身侧围为优质金属鍍锌板涨拉蒙皮
	Body frame and chassis are welded by phosphate and painted rectangular steel tube. Side panels are stretched high quality galvanized steel panels.
内饰 Interior trim	上下车位置和顶棚两侧装扶手,吊环(左10右8),平地板铺装普通地板革,全幅遮阳帘,无天窗
	On and off board handles, three-face ceiling connected handles, ring(left 10, right 8), flat floor with common vinyl, total-breath sunshade, without ceiling window
车门及门泵 Door and door pump	两个双扇手动折叠门
	Two double-leaf manual folding passenger door
车窗 Window	粘贴式半封闭铝合金侧窗
	Semi-enclosed aluminum alloy side windows
行李舱 Luggage compartment	后行李舱 Rear compartment
座椅及附件 Seat and accessories	40/22+1,可加装三个副座
	40/22+1, three attached seats can be added.
视听系统 Video and Audio	卡式收放机 Cassette studio
灯具 Lamp	组合前照灯,前顶示高灯,车身侧标志灯
	Integral front lamp, front ceiling height lamp, side mark lamp