

Auto LED Flasher YD FLL302

L×W×H(mm): 30.5×30.5×30



Features

- ┆ Suitable for flasher light during car turning;
- ┆ High sensitive and stable electronic timing;
- ┆ Wide operating voltage, temperature range and long life;
- ┆ Standard terminals, usage and Replacement easily;
- ┆ With ticking sound.

Ordering Information

<b>YD FLL302</b>			<b>- 12</b>	<b>- KT</b>
<b>1</b>	<b>2</b>	<b>3</b>		
1 Part number: YD FLL302			3 Flashing Frequency: KT: adjustable;	
2 Coil rated Voltage(VDC): 12: 12V; 24: 24V			Nil: Non-adjustable	

Technical Characteristics

Rated Voltage	12VDC, 24VDC
Operating Voltage	11VDC ~ 15VDC, 22VDC ~ 30VDC
Test Voltage	13VDC ± 0.2VDC, 26VDC ± 0.4VDC
Test Temperature	20°C ± 2°C
Switch Load	0.1W ~ 150W (0.02A ~ 20A)
Max Power	150W
Flashing Frequency	60 ~ 120 times per minute
Duty Ratio	30% ~ 70%
Operating Temperature	-40°C ~ +80°C
Life	400 working hours
Weight(Approx.)	25g

Layout (Bottom views, Unit: mm)

<p>Dimensions</p>	<p>Wiring diagram(Bottom views)</p>
-------------------	-------------------------------------