

Model 6800 Electric Mini Bus					
	Over length(mm)	6800 Motor model 0110WE			
Overall Specification  Performance Specification		2260	- Engine Specification	WOLO: MOUE!	011044
	Over width(mm)			Motor manufacturer	Shanghai Dajun power control co., Ltd (China brand)
	Over height(mm) Interior height (mm)	2850 (with AC) 1950			
	Wheelbase(mm)	5000		Position/fuel type	Rear/electricity
	Tread(mm)	1890/1680		Motor type	Permanent magnet synchronous motor (water cooling)
	Overhang F/R(mm)	910/1960		Rated power(KW/rpm)	60/1600
	Approach/Departure Angle (°)	18/11		Peak power(KW/rpm)	110/3500
	Max. speed(km/h)	69		Rated torque(N.m/rpm)	358/1600
		Rear Mounted			1000/3500
	Engine Position	Rear Mounted		Peak torque(N.m/rpm)	
	Rated passenger capacity (including driver)	45/10-19		Curb Weight(kg)	4860(With AC)
				Max. total mass(kg)	8500
Item		Standard Equipment			
Electricity Power system	Drive system	Motor	0110WE Permanent magnet synchronous motor rated voltage: 380V		
		Motor controller		ty:197KVA, maximum cap	•
		Power battery t	Ternary material lithium battery, nominal voltage:388.8V, nominal capacity: 156.8AH, 2PCS in series connection		
Chassis	Front axle	3T front axle, 17.5" disc brke			
	Rear axle	5.5T rear axle, drum brake			
	Suspension system	Less piece leaf spring(F3/R3), front and rear horizontal stabilizer bar			
	Steering system	Electric power steering sytem			
	Braking system	Double circuit pneumatic brake system, front disc and rear drum brake system, energy storage spring parking system, WABCO ABS system			
	Tyre	205/75R17.5-14PR tubeless radial tire			
	Spare tyre	One piece			
	Other	Drive motor constant temperature system			
	Accumulator	6-Q-105AH, 2 pcs			
Interior Trimming	Body structure	Monocoque			
	Interior trim	Facing material roof board, PP molding side panel, flax duct			
	Door and door pump	Front single outwards swing aluminum door, inside and outside passenger door emergency switch, passenger door emergency master switch at driver's location, left side emergency exit			
	Window, windscreen	Front cementation windscreen, rear cementation tempered windscreen, window-in-glass side window, driver front roller sunshade			
	Rear view system	BONITO rear view mirror, interior mirror			
	AC system	14000 kcal electric air conditioner			
	Defrosting system	DCS-5-WX electric defroster			
	Audio system	None			
	Wiper	Panoramic wiper (with water spray system)			
	Lamp	Independent headlights, taillights, LED roof light, door light			
	Seat	Adjustable driver seat(3-point safety belt), plastic seats with soft cushion			
	Handrail and Rings	Plastic handrails, no stationary rings			
	Paint	Domestic polyester paint			
	Others	CAN bus wire, 2 modules with cammeras, 18mm PVC floor, quartz sand floor leather, 1 pcs roof escape windows with ventilator, 2pcs 2 kg fire extinguisher, 2 pcs safety hammer, 2pcs automatic fire extinguisher in electromotor house, warndreieck, electric clock, automobile data recorder(with GPS), tool box, loud speaker			