

STAGE BACKGROUND LED CURTAIN SERIES

Module NO:	BH-S18.75-3232S-1B
Brightness	>6000 nits
Pixel pitch	18.75mm
Pixel type	SMD LEDS
Dot matrix per panel	32X32
Dot pixels per panel	1024
Dimension	W600mmXL600mm
Panel area	0,36m ²
Aspect ratio	1:1
Panel weight	5KG
Transparency	35%
Pixel type and configuration	SMD 5050
Protection level	IP65
Dot pixels per sqm	2844
Operating temperature range	-30℃ -60℃
Viewing angle	110°/110°±5°(Vert./Horz)
Color temperature	6500K
Contrast ratio	1000:1
Panel material	Plastic with aluminum frame
Drive mode	constant current drive static
Minimum viewing distance	14 m
Color depth	16bit
Greyscale(liner)levels	64k levels per color
Refresh rate	1920HZ
System type	Computer synchronous
Computer video frame rate	50/60HZ
Power consumption	Max.650W per square meter
Input voltage	AC 90-260V
Lifetime(50% brightness)	>80,000 hours
Mounting system	Rear hanging,fix installation

SHENZHEN **BORCCO** TECHNOLOGY CO., LTD.

No.15 ChaoYang RD, Bldg 3, 4/F, BYF Science and Technology Park, Yanchuan, Songgang, Baoan, Shenzhen, China 518105

TEL: +86 755 33238588

FAX: +86 755 33234370

WEB: www.borcco.com