

Product features

- Low start up wind speed, compact, light, beautiful and with little vibration.
- 2. Easy installation, flange connection.
- Blades using nylon fiber matched with optimized aerodynamic shape and structure.
 Color optional.
- 4.Patented permanent magnet ac generator with special stator(maglev generator), effectively reduce torque, make only 1/3 torque of ordinary generator, well match the wind wheel and generator, and ensure the performance of whole system.

■ Technical parameter

Model	NE-100RV	NE-200RV	NE-300RV
Rated power	100W	200W	300W
Maximum power	130W	220W	310W
Rated voltage	12V/24V	12V/24V	12V/24V
Start up wind speed	2m/s	2m/s	2m/s
Rated wind speed	11m/s	11m/s	12m/s
Survival wind speed	45m/s	45m/s	45m/s
Top net weight	11kg	11.5kg	12kg
Wheel diameter	0.9m	0.9m	0.9m
Wheel height	0.6m	0.6m	0.6m
Blades number	5		
Blades material	Nylon fiber		
Generator	Three phase permanent magnet ac generator/ maglev generator		
Control system	Electromagnet		
Speed regulation	Automatically windward		
Working temperature	-40°C ~ 80°C		

Remarks: above data are for sales reference,not as part of contract,the company reserves the right to make changes without any further notice.

The forces of nature, leads to new course of energy

NAI ER WIND POWER