



SHANGHAI UPG INTERNATIONAL TRADING CO., LTD



LQY-330/450 Stacked Flexographic Presses

Add: Room 2403 Jincheng Mansion 511 Tianmuxi Road, 200070 P.R.China

TEL: 86-21-63177436 FAX: 86-21-63538343

Email: liulingyuan@shanghai-upg.com



LQY-330/450 Stacked Flexographic Presses

1.Quotation:

LQY-330/450 USD/unit (FOB SHANGHAI)

2.Terms of Payment:

30% deposit by T/T when confirming the order

70% balance by T/T before shipping.

3.Performance of the machine:

- 1)The main motor adopts imported inverter to govern a stepples speed adjustment.
- 2) The printing units are all equipped with a group of infrared dryers respectively .
- 3) Each IR dryer device of printing unit is interchangeable to UV dryer.
- 4) Feeding and rewinding are controlled through magnetic particle brake and clutch (Japanese Mitsubishi auto tension controller).
- 5)Un winder and re winder adopt air core holder.
- 6)Three unit rotary cut with stand-roller make multi-cut can be processed
- 7)Adopt ceramic anliox roller which offers durability, wear resistance and corrosion resistance, also is more efficient on production by reducing the times of changing rollers.
- 8)The printing unit can register in 360 degrees. Each printing unit can be independently geared and loosen to have rest of units continue to printing.8
- 9)The inking roller will be automatically off impression when press stop and rotate at lower speed in order to keep the ink from being drying.
- 10)Paper unwind, printing, UV vanish, laminating, rotary diecutting, waste removal and rewinding can be processed in one pass. It has characterized by wide application, fast printing speed and high economic efficiency ink will not contaminate environment. So it is an idea printing machine for the business form, Tag and high end pressure sensitive label.

4.Specifications:

Model	LQY-330	LQY-450
Max. web width	330mm	450mm
Max.printing width	320mm	440mm
Printing repeat	180mm-380mm/min	180mm-380mm/min
Color	2-6colors	2-6colors
Thickness of substrate	0.1-0.3mm	0.1-0.3mm
Machine speed	10m-80m/min	10m-80m/min
Max. unwind diameter	650mm	650mm
Max. rewind diameter	650mm	650mm
Rotary-cutting stations	3	3
Main motor capacity	2.2kw	2.2kw
Main power	380V/AC Three-phase 50HZ	380V/AC Three-phase 50HZ
Overall dimension(L×W×H)	2420*1020*2740mm	2420*1020*2740mm
Machine weight	2500kg/5colors	3000kg/5colors

5.Optionals

- 1)Single stacker
- 2)UV curing unit
- 3)Machine color
- 4)Cold foil

