

Model	WSER-1000	WSER-1500	WSER-2000	WSER-3000	WSER-5000	WSER-8000	WSER-10000	
Rated Capacity	1000VA	1500VA	2000VA	3000VA	5000VA	8000VA	10000VA	
Phase	Single							
Transformer	C.R.G.O. toroidal transformer							
Indicator	LED graphic							
Display Status	working and loading							
Input	Voltage	140~260 Vac						
	Frequency	50/60 Hz						
Output	Voltage	110/120/220/230/240 Vac optional						
	Precision	±8%						
Protection	Overload	Yes						
	High temperature	Yes						
	High/low voltage	Yes						
	Short circuit	Yes						
Delay Function	delay / un-delay (180/6 seconds selectable)							
Efficiency	98%							
Cooling system	Smart cooling for 3000Va and above							
Environmental	Operating temperature	0 - 40 °C						
	Relative humidity	10%~102% RH, non-condensing						
	Storage temperature	- 15 - 45 °C						
Appearance	AVR size (mm)	170x120x205			200x120x320		255x165x320	
	AVR N.W. (kg)	3.00	3.40	3.70	6.80	7.80	10.60	12.30
	Inner box size (mm)	210x160x245			240x160x360		295x205x360	
	Qty/Ctn	4			2		1	
	Carton size (mm)	500x220x330			730x250x170		295x205x360	
	Carton G.W. (kg)	13.80	15.60	16.60	15.20	17.20	11.40	13.10