



SOALR SYSTEM CONFIGURATION

PRODUCTION NAME	Solar panel	Battery	Controller	Inverter
SPECIFICATIONS	250w 24v	12v200AH	24v40A	1.5 KW
QUALITY	4	4	1	1

MAIN FEATURE

1. FOR three rainy , cloudy days
2. Systems include: solar panels, controller, inverter, stenting, cable, accumulator
3. short-circuit protection. Overload, reverse protection,
4. Sunshine condition: sunshine 10 hours a day, effectively peak sunshine 5hours a day
5. environment: -45 °C +65 °C

SUPPLIER'S QUOTATION AND SPECIFICATIONS AND WARRANTY

PRODUCT DESCRIPTION	SPECIFICATIONS	QUALITY	TOTAL: Fob USD	SUPPLIER	PARAMETERS	LIFE SPAN (YEARS)	WARRANTY (YEAR)
Solar panel	24v250w	4	800	Sopray		12years 90% 25years 80%	10
Controller	24v40A	1	115	Sopray	short-circuit protection, reverse protection, overloadSOC	10	1
Inverter	1.5 KW	1	240	Sopray	high than 90%	10	1
Battery	12v200AH	4	980	Sopray	maintenance-free lead-acid batteries, deep release 600 times.	5	1
Accessories	260		260		structure of solar panel , cable	20-25	1