

<b>MODEL</b>	<b>RH-XC08-03B</b>		
PURIFICATION	Hollow-fiber ultrafiltration		
WATER	OUTPUT	HOT WATER	yes
		ROOM TEMP WATER	yes
		COLD WATER	yes
	INPUT	Tap water	
WATER PRESSION IN	MIN	0.2Kgf/cm2	
	MAX	4.0Kgf/cm2	
FILTER	PP FILTER (10u)/	yes	
	PRECARBON	yes	
	UF MEMBRANE	yes	
	RO MEMBRANE	no	
	POST CARBON	yes	
TANK CAPACITY	ROOM WATER	4.8L minimum	
	HOT WATER	1.4L	
	COLD WATER	2.3L minimum	
CAPACITIES	COLD WATER	4.0L/hour	
	HEATING POWER	500w	
	FILTRATION	50L/H	
REFRIGERATION	COMPRESSOR	Yes	
	KIND OF GAS	R134a	
ELECTRONICS	LEDS/LED	yes	
	AUTO SHUT DOWN	yes	
	WATER PUMP	no	
	SOLENOID VALVE	yes	
DIMENSIONS(MM)	Packing dimensions (mm)	509*334*1213	
	Net dimensions( mm)	459*290*1150	
GROSS WEIGHT		28.5kg	
POWER	POWER	110v, 60hz or 220v, 50hz	
	PLUG	upon request	
CERTIFICATION	ISO9001:2000	yes	
	CB	yes	
	CE	yes	
CONTAINER LOADING QTY	20GP		
	40HQ	320pcs (40'HQ)	