

Solar DC Direct Drive 4SK Series

Solar Direct Driver Single Phase Pump 4SK 4.0 Series (4Ton/H)

Type : 4SK Series Single Phase Solar Pump System

Model	Capacity	MPPT Voltage	Open Voltage	Rated Head	Max. Head	Max. Flow	Water Inlet	Water outlet	Protection Level
	W	V	V	m	m	T/H	mm	Inch	
4SK4/8-0.55	550	160V-180V	230V	40	58	4	100	1.5/2	IP68
4SK4/10-0.75	750	160V-180V	230V	50	72	4	100	1.5/2	IP68
4SK4/14-1.1	1100	160V-180V	230V	70	101	4	100	1.5/2	IP68
4SK4/18-1.5	1500	160V-180V	230V	90	130	4	100	1.5/2	IP68

solar direct driver single phase pump 4SK 6.0 series (6Ton/H)

Type : 4SK series single phase solar pump system

Model	Capacity	MPPT Voltage	Open Voltage	Rated Head	Max. Head	Max. Flow	Water Inlet	Water outlet	Protection Level
	W	V	V	m	m	T/H	mm	Inch	
4SK6/7-0.55	550	160V-180V	230V	26	46	6	100	1.5/2	IP68
4SK6/9-0.75	750	160V-180V	230V	33	59	6	100	1.5/2	IP68
4SK6/12-1.1	1100	160V-180V	230V	44	79	6	100	1.5/2	IP68
4SK6/15-1.5	1500	160V-180V	230V	55	98	6	100	1.5/2	IP68

solar direct driver single phase pump 4SK 8.0 series (8Ton/H)

Type : 4SK series single phase solar pump system

Model	Capacity	MPPT Voltage	Open Voltage	Rated Head	Max. Head	Max. Flow	Water Inlet	Water outlet	Protection Level
	W	V	V	m	m	T/H	mm	Inch	
4SK8/5-0.55	550	160V-180V	230V	20	32	8	100	1.5/2	IP68
4SK8/7-0.75	750	160V-180V	230V	28	45	8	100	1.5/2	IP68
4SK8/9-1.1	1100	160V-180V	230V	36	58	8	100	1.5/2	IP68
4SK8/12-1.5	1500	160V-180V	230V	49	77	8	100	1.5/2	IP68

solar direct driver single phase pump 4SK 10.0 series (10Ton/H)

Type : 4SK series single phase solar pump system

Model	Capacity	MPPT Voltage	Open Voltage	Rated Head	Max. Head	Max. Flow	Water Inlet	Water outlet	Protection Level
	W	V	V	m	m	T/H	mm	Inch	
4SK10/4-0.55	550	160V-180V	230V	13	24	10	100	1.5/2	IP68
4SK10/6-0.75	750	160V-180V	230V	20	36	10	100	1.5/2	IP68
4SK10/8-1.1	1100	160V-180V	230V	27	48	10	100	1.5/2	IP68
4SK10/10-1.5	1500	160V-180V	230V	34	60	10	100	1.5/2	IP68

Solar DC Direct Drive 4SK Series

Note:

- with high voltage detection and protection, under voltage protection, blocking protection, over current protection, lack of water protection, water pump built-in CPU, unattended operation, intelligent control.
- the pump body is stainless steel 304 structure.
- pump with 5 meters of cable, the cable length can be customized according to customer requirements, according to the different diameter in accounting.
- according to the use of the sunshine state, matching components of the power = pump power *1.0-1.5.

