

TER series

| Model | TER-1000 | TER-1500 | TER-2000 | TER-3000 | TER-5000 | TER-8000 | TER-10000 | |
|----------------|---|----------------------------------|----------|----------|-------------|----------|-----------|-------|
| Rated Capacity | 1000VA | 1500VA | 2000VA | 3000VA | 5000VA | 8000VA | 10000VA | |
| Phase | Single | | | | | | | |
| Transformer | C.R.G.O. toroidal transformer | | | | | | | |
| Indicator | LED graphic | | | | | | | |
| Display Status | working and loading | | | | | | | |
| Input | Voltage | 100~260 Vac | | | | | | |
| | Frequency | 50/60 Hz | | | | | | |
| Output | Voltage | 110/120/220/230/240 Vac optional | | | | | | |
| | Precision | ±8% | | | | | | |
| | Overload | Yes | | | | | | |
| Protection | High temperature | Yes | | | | | | |
| | High/low voltage | Yes | | | | | | |
| | Short circuit | Yes | | | | | | |
| Delay Function | delay / un-delay (180/6 seconds selectable) | | | | | | | |
| Efficiency | 98% | | | | | | | |
| Cooling system | Smart cooling for 3000Va and above | | | | | | | |
| Environmental | Operating temperature | 0 - 40 °C | | | | | | |
| | Relative humidity | 10%~102% RH, non-condensing | | | | | | |
| | Storage temperature | - 15 - 45 °C | | | | | | |
| Appearance | AVR size (mm) | 230x145x180 | | | 355x220x250 | | | |
| | AVR N.W. (kg) | 3.10 | 3.60 | 3.80 | 6.80 | 8.10 | 10.90 | 12.60 |
| | Inner box size (mm) | 293x190x225 | | | 395x272x305 | | | |
| | Qty/Ctn | 4 | | | 1 | | | |
| | Carton size (mm) | 785x305x240 | | | 395x272x305 | | | |
| | Carton G.W. (kg) | 14.10 | 15.90 | 17.10 | 7.60 | 8.90 | 11.70 | 13.40 |