

Model	SHC 130v-270v~	SHC-1000	SHC-1500	SHC-2000	SHC-3000	SHC-5000	SHC-8000	SHC-10000
	THC 110v-270v~	THC-1000	THC-1500	THC-2000	THC-3000	THC-5000	THC-8000	THC-10000
Rated Capacity		1000VA	1500VA	2000VA	3000VA	5000VA	8000VA	10000VA
Phase		Single						
Transformer		C.R.G.O. toroidal transformer						
Indicator		LED graphic						
Display Status		working and loading						
Output	Frequency	50/60 Hz						
	Voltage	110/120/220/230/240 Vac optional						
	Precision	± 1%-3%						
Protection		overload / high temperature / high voltage / low voltage / short circuit						
Delay Function		delay / un-delay (180/6 seconds selectable)						
Efficiency		98%						
Cooling System		Smart cooling for 3000Va and above						
Environmental	Operating Temperature	0 - 40 °C						
	Relative Humidity	10%~102% RH, non-condensing						
	Storage Temperature	- 15 - 45 °C						
Appearance	Size (Max. mm)	240x146x180			355x220x250			
	N.W. (kg) SHC	3.90	4.30	4.60	7.7	8.7	11.7	13.7
	N.W. (kg) THC	4.40	4.80	5.10	8.2	9.2	12.2	14.2
Packing	Qty/Ctn	4			1			
	Carton Size (mm)	785x305x240			395x272x305			
	Carton G.W. (kg) SHC	17.60	19.20	20.40	8.50	9.50	12.50	14.50
	Carton G.W. (kg) THC	19.60	21.20	22.40	9.00	10.00	13.00	15.00