

## Description

Applications: To suit glueless film and pre-glued film

- . Automatic paper feeder adopts oil-free vacuum pump to feed paper automatically.

- . Automatic paper feeding system is equipped with no paper protector and paper break protector, which are controlled by photoelectric and mechanical systems. When no paper or paper break occurs, the machine will stop automatically for self-protection.

- . Man-machine interface system: color touch screen simplifies the machine operation. On the touch screen, as long as the operator inputs paper size, overlap length and working speed etc., The machine can realize completely automated operation. And on touch screen, working status of the machine can be checked at any time.

- . Conveying table is furnished with air aspirator and front lay etc. to guarantee paper conveying and overlap stable and regular.

- . High precision of chrome plated heating roller is equipped with built-in oil heating system, which has excellent performance to temperature control. The laminating temperature is adjustable upon applications.

- . Hydraulic pressuring system provides automatically big and steady pressure to guarantee good laminating quality.

- . Air expansion shaft releases film, and precisionists film release, and also makes the loading and unloading of film roll more convenient

- . The combination of air expansion shaft and braking device can adjust film release tension and speed.

- . Anti-curvature device: when going through the anti-curvature device, the laminated paper shall be leveled at once and won't curve again after cut

- . Paper receiving unit is furnished with not only vibrating receiving table but also winding roller. After cut, the laminated paper will be sent automatically to vibrating receiving table and be put into order. If laminated paper doesn't need to be cut, it can be winded automatically by winding roller.

Specifications

Model	SAFM-800A
Max Paper Size	780×1040mm
Min Paper Size	300×300mm
Laminating Speed	0-50m/min
Paper Thickness	100-500gsm
Gross Power	18kw
Overall Dimensions	5300×1630×1650mm
Weight	2500kgs