Machine		INFRARED IC HEATER			LED New Light Source Reflow Oven
Mode1		T-962	T-962A	T-962C	T-960
		Puhui File 8 File 8	Puhui CE	pyhui (€	pyhui CE
Power Voltage		AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/380V 50Hz
Mode Of Heating		infrared emission and circulation of the hot air flow	infrared emission and circulation of the hot air flow	infrared emission and circulation of the hot air flow	intelligent level sirocco and rapid infrared heating
Rated power		800W	1500W	2500W	4500W
Cycle Time		1∼8 min	1∼8 min	1∼8 min	Net transmission+chain transmission
Mode Of Controling		8 Intelligent temperature waves heating	8 Intelligent temperature waves heating	8 Intelligent temperature waves heating	8 Intelligent temperature waves heating
Temperature Range		0−280℃	0−280°C	0−280℃	Room temperature∼300℃
Soldering PCB Area		180X235mm	300X320mm	400X600mm	Limit Wide:300mm
Package	Dimensions	310X290X170mm	430X370X260mm	684X504X225mm	$1450\!\times\!630\!\times\!470\text{mm}$
	Package size	375X240X375mm	510X330X450mm	780X600X330mm	1500X900X650mm
	Weight	7Kgs	15Kgs	27Kgs	130kgs