

Specifications

Operating Voltage	3.0V DC; 1 pc. CR2032 lithium coin type
Operating Current	Min. 10 μ A; Max. 140 μ A.
Ambient temperature display	-30 $^{\circ}$ C to 70 $^{\circ}$ C
Accuracy	± 2 $^{\circ}$ C (-30 $^{\circ}$ C \sim 0 $^{\circ}$ C)
	± 1 $^{\circ}$ C (0 $^{\circ}$ C \sim 70 $^{\circ}$ C)
Over range Temperature display	> 70 $^{\circ}$ C “HI”; < -30 $^{\circ}$ C “LO”
Ambient Humidity reading and accuracy	25% to 90% RH ($\pm 5\%$ within 0 $^{\circ}$ C \sim 40 $^{\circ}$ C)
Resolution	0.1 $^{\circ}$ C / 1% RH
Over range Humidity display	< 25% approx. “LO”; > 95% approx. “HI”
Storage Temperature and Humidity	-5 $^{\circ}$ C \sim 60 $^{\circ}$ C / < 80% RH
Reading response time	3 seconds
With key chain holder	Yes
Battery powered	3V x 1 piece coin type (CR2032)
Weight (approx.) grams	24
Dimension (L x W x D) mm	50 x 42 x 15