



SHANGHAI UPG INTERNATIONAL TRADING CO., LTD



WIN504 Two-color offset press

Add: Room 2403 Jincheng Mansion 511 Tianmuxi Road, 200070 P.R.China

TEL: 86-21-63177436 FAX: 86-21-63538343

Email: grace@shanghai-upg.com

WIN504 Two-color offset press



Performance:

- 1) Heavy duty mechanism structure. Cast iron pedestal. frame、cylinders etc. have the good and intension and tenacity, ensuring high stability and good printing impression.
- 2) Underswing feeder, paper transferring structure is used high point gripper closed structure, insuring paper transferring system more stably.
- 3) Double diameter impression cylinder and triple diameter transferring cylinder are available, reducing the times of paper connection, improving register precision.
- 4) Plate cylinder and blanket cylinder go through with bearer, running stably, ensuring qualified printing image.

Specification

Model	WIN504
Max. Paper Size	500 x 365 (mm)
Min. Paper Size	130 x 184 (mm)
Paper Thickness	0.04-0.3 (mm)
Max. Printing Area	470 x 350 (mm)
Printing Speed	3000-9000(s/h)
Plate Size	490 x 412 (mm)
Plate Clamp Type	Straight edge plate clamp
Blanket Size	496 x 472 x 1.9 (mm)
Feeder Pile Capacity	450 (mm)
Delivery System	Chain delivery
Delivery Pile Capacity	510 (mm)
Registration System	Roll pull guide
Number of Rollers	Ink rollers 16 Water rollers 6

Gripper Margin	8 (mm)
Vertical Image Adjustment Range	± 2 (mm)
Lateral Image Micro Adjustment Range	± 2 (mm)
Graphic oblique micro-adjustment range	± 0.15 (mm)
Oiling System	Automatic centralized oiling system
Power source	380V/50Hz 3kw/0.75kw
Dimensions L x W x H(mm)	3600 x 1070 x 1600
Net Weight	3800 (kg)