Portable Bluetooth Thermal Printer Series

Model: DP-BM9000II

58mm portable thermal printer

Specifications	
Specifications:	
Dimension(W x L x H)	74*104*45mm
Print method	Thermal Dot Line Printer
Paper width	57.5± 0.5mm
Print width	48mm
Weight (g)	250 (not including the paper roll)
Max diameter of paper roll	40mm
Dot per lie	384 dots/line
Internal characters	ANK: 9x17,12×24; GBK: 24×24
Print speed	50~80mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
	English,figure,symbol,Chinese,graph,curve,iconpre-stored,
Text and graphic Support	barcode(CODE39/EAN13/EAN8/CODABAR/CODE128/CODE93/ITF),
	QR code, PDF417
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	1) USB + serial + single bluetooth (android)
	2) USB + serial + single bluetooth (ios)
	3) USB + double bluetooth (android + ios)
Power	2000mAh 7.4V rechargeable Lithium battery
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper /cover open
Black mark test	Supported
Paper feeding	Easy paper loading
Commands	ESC/POS compatible with order sets
Paper cut	By hands
Operate setting	Temperature: -10°C~50°C; Humidity: 20%~85%
Recharge Setting	Temperature: 5°C~40°C; Humidity: 20%~85%
Storage Setting	Temperature: -20°C~70°C; Humidity: 5%~95%
Standard accessories	Roll paper, AC adapter, li-ion battery,user manual
Optional accessories	Serial interface cable, USB cable, car charger, leather cover



Feature:

- ★ Portable device suited for outdoor usage
- ★ Black mark paper location sensor
- ★ Low battery indicator(7.4V,2000mAh)
- ★ Equipped with lithium battery for 4-8 hours continuous work
- ★ Vairous interface communication and interface capabilites
- ★ Bluetooth with high communication speed
- ★ Easy paper loading
- ★ High printing speed , up to 80mm/s.

Application:

- ♦ Mobile POS/Retail
- Hospitality
- ◆ Packing citation
- Deliveries
- ◆ Onboard Transportation
- ◆ Field reparts/Installation
- ♦ Warehouse/logistics
- ◆ Utility billing/meter reading