

三相制动电机

Three-Phase Brake Motor

性能特点:

- 功率: 1/3HP-2HP
- 极数: 4P
- 机座: 56C
- 防护形式: 封闭式
- 防护等级: IP44
- 服务系数: 1.15
- 该电机适用于有制动要求的场合
如快速停车、升降机、卷扬机等
- 所有电机都有 CSA & CUS 认证

Features:

- HP: 1/3HP-2HP
- Pole:4P
- Frame: 56C
- Enclosure: TEFC
- IP Class: IP44
- Service Factor:1.15
- Apply to Auto requirement situations, such as:
sudden parking, elevator, windlass, etc
- CSA&CUS certified

HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	1800	56C	F56C1/3M4A-2	230/460	60	TEFC	1.15	1.64/0.82	26
	1800	56C	F56C1/3M4D-2	575	60	TEFC	1.15	0.66	26
1/2	1800	56C	F56C1/2M4A-2	230/460	60	TEFC	1.15	2.2/1.1	29
	1800	56C	F56C1/2M4D-2	575	60	TEFC	1.15	0.88	29
3/4	1800	56C	F56C3/4M4A-2	230/460	60	TEFC	1.15	2.8/1.4	32
	1800	56C	F56C3/4M4D-2	575	60	TEFC	1.15	1.12	32
1	1800	56C	F56C1M4A-2	230/460	60	TEFC	1.15	3.6/1.8	37
	1800	56C	F56C1M4D-2	575	60	TEFC	1.15	1.45	37
1.5	1800	56C	F56C1.5M4A-2	230/460	60	TEFC	1.15	4.8/2.4	41
	1800	56C	F56C1.5M4D-2	575	60	TEFC	1.15	1.92	41
2	1800	56C	F56C2M4A-2	230/460	60	TEFC	1.15	5.8/2.9	44
	1800	56C	F56C2M4D-2	575	60	TEFC	1.15	2.1	44