

- > H2000 系列内燃
- > H2000 SERIES INTERNAL COMBUSTION TRUCK

3-3.5t

内燃平衡重式叉车 Internal Combustion Counterbalanced Forklift Truck

H2000-internal combustion



型号	model		CPC30	CPC30
动力种类	power type		柴油 Diesel	柴油 Diesel
额定起重量	rated capacity	Kg	3000	3000
载荷中心距	load center	mm	500	500
货叉最大高度(带挡货架)	mast height,extended(with backrest)	mm	4262	4262
最大起升高度	max. fork height	mm	3000	3000
自由起升高度	free lift height	mm	160	160
全高(护顶架)	overall height(overhead guard)	mm	2090	2090
全长(带货叉)	overall length(with fork)	mm	3772	3772
全宽	overall width	mm	1225	1225
最小离地间隙(门架处)	min. ground clearance(at the mast)	mm	135	135
最小转弯半径(外侧)	min. turning radius(exterior)	mm	2400	2400
最小直角通道宽度	min. right angle stacking aisle width	mm	2380	2380
货叉尺寸(长x宽x厚)	fork size(length x width x thickness)	mm	1070x125x45	1070x125x45
最大行驶速度(满/空载)	max. travelling speed(loaded/unloaded)	Km/h	18/19	18/19
最大牵引力(满/空载)	max. traction force(loaded/unloaded)	KN	14.5/9.8	16.5/9.8
最大爬坡能力(满/空载)	max. gradeability(loaded/unloaded)	%	17/20	24/20
轮胎类型(前/后)	tyre type		2/2	2/2
发动机制造商/型号	engine mode		全柴QC490GP Quanchai QC490GP	全柴QC490GP Quanchai QC490GP
额定功率	rated power	KW/rpm	39/2650	39/2650
额定扭矩	rated torque	Nm/rpm	162/1950	162/1950
总重(含油水)	total weight(oil included)	kg	4270	4270

可选配发动机 Optional Engine Model				
发动机型号 engine model	额定功率/转速(KW/rpm) rated power/rotational speed	额定扭矩(Nm/rpm) rated torque	发动机排量(L) engine displacement	发动机缸数 engine cylinder NO.
新昌498 Xinchang 498	45/2500	193/1800	3.168	4
GM3.0 LPG	50/2700	203/1400-1600	3.0	4
GM3.0 GAS	55/2700	191.5/1400-1600	3.0	4

CPC35	CPCD35	CPC30	CPCD30	CPC35	CPC35
柴油 Diesel	柴油 Diesel	汽油或液化石油气 gasoline or LPG	汽油或液化石油气 gasoline or LPG	汽油或液化石油气 gasoline or LPG	汽油或液化石油气 gasoline or LPG
3500	3500	3000	3000	3500	3500
500	500	500	500	500	500
4262	4262	4262	4262	4262	4262
3000	3000	3000	3000	3000	3000
170	170	160	160	170	170
2090	2090	2090	2090	2090	2090
3783	3783	3772	3772	3783	3783
1225	1225	1225	1225	1225	1225
135	135	135	135	135	135
2420	2420	2400	2400	2420	2420
2400	2400	2380	2380	2400	2400
1070x125x50	1070x125x50	1070x125x45	1070x125x45	1070x125x50	1070x125x50
19/19	19/19	18/19	18/19	19/19	19/19
16.7/11.8	20.6/11.8	13.5/9.8	16/9.8	14/9.8	18.5/9.8
15/20	19/20	15.5/20	23/20	15/20	18/20
2/2	2/2	2/2	2/2	2/2	2/2
全柴QC490GP Quanchai QC490GP	全柴QC490GP Quanchai QC490GP	新昌A490BPG-76 Xinchang A490BGP-76	新昌A490BPG-76 Xinchang A490BGP-76	新昌A490BPG-76 Xinchang A490BGP-76	新昌A490BPG-76 Xinchang A490BGP-76
39/2650	39/2650	36.8/2560	36.8/2560	36.8/2560	36.8/2560
162/1950	162/1950	148/1900	148/1900	148/1900	148/1900
4700	4700	4270	4270	4700	4700