



WOYR2.E88833 Switches, Appliance and Special Use - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Switches, Appliance and Special Use - Component

[See General Information for Switches, Appliance and Special Use - Component](#)

ELECTRICAL DEVICES INC

E88833

1850 WILSON AVE

WESTON, ON M9M 1A1 CANADA

Cat. No.	Amps	Volts	Hz	Load	Endurance	Temp C	POL/THR	Per Pole/Circuit Code	SPCOA
7536K20 thru -29									
	10	125	60	GP	6K	105	1/M	-/-	-
	5	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
7537K20, 7537K-21									
	15	125	60	GP	6K	105	1/M	-/-	-
	10	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
7537K22, 7537K-25, 7537K-28									
	10	125-250	60	1/2hp	6K	105	1/M	-/-	-
7537K23, 7537K-24, 7537K26, 7537K27									
	15	125	60	GP	6K	105	1/M	-/-	-
	10	250	60	GP	6K				
	-	125-250	60	1hp	6K				
8020K20 thru -28									
	10	125	60	GP	6K	105	1/M	-/-	-
	5	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
8020K29 thru -34									
	10	125	60	GP	6K	105	1/M	-/-	-
	5	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
8021K20, 8021K-21, 8021K-22									
	15	125	60	GP	6K	105	1/M	-/-	-
	10	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
8021K23 thru -28									
	15	125	60	GP	6K	105	1/M	-/-	-

	10	250	60	GP	6K				
	-	125-250	60	1hp	6K				
8023K26	15	125	60	GP	6K	105	1/M	-/-	-
	10	250	60	GP	6K				
	-	125-250	60	1hp	6K				
	3	277	60	GP	6K				
8024K-20, 8024K-21, 8024K-22									
	10	125	60	GP	6K	105	1/M	-/-	-
	5	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
8025K-20, 8025K-21,									
	15	125	60	GP	6K	105	1/M	-/-	-
	10	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
8025K-22	10	125	60	GP	6K	105	1/M	-/-	-
	10	250	60	GP	6K				
	-	125-250	60	1/2hp	6K				
8946K805	1	125	60	GP	6K	105	1/2	-/-	A1
	1	125	DC	-	6K				
8946K806	1	125	60	GP	6K	105	1/1	-/-	-
HP-02	4	125	60	GP	6K	65	1/1	-/A	Note 2
	2	250	60	GP	6K				
HPS-1104	4	125	60	GP	6K	65	1/1	-/A	-
	2	250	60	GP	6K				
HPS-1306 f/b - A thru G									
	5	125	60	GP	6K	65	1/M	-/A	Note 1
	3	250	60	GP	6K				
HR-02 f/b A, B, or C									
	6	125	60	GP	6K	65	1/1	-/A	-
	3	250	60	GP	6K				
HR-02-P f/b A, B, or C									
	6	125	60	GP	6K	65	1/1	-/A	6(18)
	3	250	60	GP	6K				
HR-03 f/b A, B, or C									
	6	125	60	GP	6K	65	1/M	-/A	Note 1
	3	250	60	GP	6K				
HR-03-P f/b A, B, or C									
	6	125	60	GP	6K	65	1/M	-/A	6(18), Note 1
	3	250	60	GP	6K				
HR-03-P-A2	6	125	60	GP	6K	65	1/M	-/A	6(18), Note 1
	3	250	60	GP	6K				
HR-04	6	125	60	GP	6K	65	1/M	-/A	6(18), Note 1


	3	250	60	GP	6K				
HR-04-A	6	125	60	GP	6K	65	1/M	-/A	6(18), Note 1
	3	250	60	GP	6K				
HR-04-B	6	125	60	GP	6K	65	1/M	-/A	6(18), Note 1
	3	250	60	GP	6K				
HR-04-C	6	125	60	GP	6K	65	1/M	-/A	6(18), Note 1
	3	250	60	GP	6K				
HSA-1201-0	1	125	60	GP	6K	80	1/2	-/A	3
	0.5	250	60	GP	6K				
HSA-1201-R	1	125	60	GP	6K	80	1/2	-/A	3
	0.5	250	60	GP	6K				
HSA-1201-Y	1	125	60	GP	6K	80	1/2	-/A	3
	0.5	250	60	GP	6K				
HSA-2201-0	1	125	60	GP	6K	80	2/2	-/B	3, Note 3
	0.5	250	60	GP	6K				
HSA-2201-R	1	125	60	GP	6K	80	2/2	-/B	3, Note 3
	0.5	250	60	GP	6K				
HSA-2201-Y	1	125	60	GP	6K	80	2/2	-/B	3, Note 3
	0.5	250	60	GP	6K				
HSB-1206	6	125	60	GP	6K	80	1/2	-/A	3
	3	250	60	GP	6K				
HSB-2206	6	125	60	GP	6K	80	2/2	-/B	3, Note 3
	3	250	60	GP	6K				
HTA-1115-WT	10	125	60	GP	6K	65	1/1	-/A	Note 2
	10	250	60	GP	6K				

Note 1 - For multiple throw switches, the maximum current for the COMMON terminal should not exceed the rated current at the respective voltage.

Note 2 - The switch is provided with 18 AWG wire leads which were used for the Temperature Test. The routing and strain relief have not been evaluated during the switch investigation and will need to be evaluated during the end product investigation.

Note 3 - Double pole switch models were tested using Circuit B. If end-product requires connections as in Circuit D, further testing is required.

Marking: Markings on the switch body consist of at least items (a) and (b) or (c) as noted below (other markings shall be on the smallest shipping package):

- (a) Manufacturer's identifier (such as name or tradename "EDI" , as described in the UL file)
- (b) Electrical ratings
- (c) Catalog or model number (or equivalent)
- (d) Factory code (as described in the UL Report, if more than one location)
- (e) Recognized Component Mark, 

Last Updated on 2010-11-18

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".