

MODEL	SBW-50KVA	SBW-75KVA	SBW-100KV A	SBW-150KVA	SBW-200KVA
	SBW-250KVA	SBW-320KV A	SBW-400KV A	SBW-500KVA	SBW-600KVA
TECHNOLOGY	SERVO MOTOR CONTROL SYSTEM				
DISPLAY	METER	A/B/C PHASE INPUT VOLTAGE			
		A/B/C PHASE OUTPUT VOLTAGE			
		A PHASE OUTPUT CURRENT			
		B PHASE OUTPUT CURRENT			
		C PHASE OUTPUT CURRENT			
	Light	Green	A PHASE WORKING INDICATOR		
		Green	B PHASE WORKING INDICATOR		
		Green	C PHASE WORKING INDICATOR		
		Green	INPUT WORKING INDICATOR		
		Green	INPUT WORKING INDICATOR		
Language	English/Russia/Chinese				
Input Voltage	Single phase:175V-265V Three phase four-line 175V-265V(phase voltage)300V-465V (line voltage) 154V-286V(phase voltage) 270V-490v(line voltage)				
Output Voltage	Single phase 220V(Adjustable) three phase 380V(adjustable)				
Frequency	50Hz/60Hz				
Phase	Thee phase				
Efficiency	90%				
Ambient Temperature	-15℃-45℃				
Relative humidity	<95%				
Waveform distortion	No additional wave from distortion				
Insulation resistance	Normally more than 2M				

Power	50KVA	75KVA	100KVA	150KVA	200KVA
Packing size(cm)	50*62*135	50*62*135	85*62*150	100*72*170	100*72*200
Packing (pcs)	1	1	1	1	1
G.M(KG S)					
Power	250KVA	320KVA	400KVA	500KVA	600KVA
Packing size(cm)	110*80*200	110*80*210	200*160*420	200*160*420	200*160*420
Packing (pcs)	1	1	1	1	1
G.M(KG S)					