

Model		SER-1000	SER-1500	SER-2000	SER-3000	SER-5000	SER-8000	SER-10000
Rated Capacity		1000VA	1500VA	2000VA	3000VA	5000VA	8000VA	10000VA
Phase		Single						
Transformer		C.R.G.O. toroidal transformer						
Indicator		LED graphic						
Display Status		working and loading						
Input	Voltage	140~260 Vac						
	Frequency	50/60 Hz						
Output	Voltage	110/120/220/230/240 Vac optional						
	Precision	±8%						
Protection	Overload	Yes						
	High temperature	Yes						
	High/low voltage	Yes						
	Short circuit	Yes						
Delay Function		delay / un-delay (180/6 seconds selectable)						
Efficiency		98%						
Cooling system		Smart cooling for 3000Va and above						
Environmental	Operating temperature	0 - 40 °C						
	Relative humidity	10%~102% RH, non-condensing						
	Storage temperature	- 15 - 45 °C						
Appearance	AVR size (mm)	230x145x180			355x220x250			
	AVR N.W. (kg)	3.00	3.40	3.70	6.80	7.80	10.60	12.30
	Inner box size (mm)	293x190x225			395x272x305			
	Qty/Ctn	4			1			
	Carton size (mm)	785x305x240			395x272x305			
	Carton G.W. (kg)	13.80	15.60	16.60	7.60	8.60	11.40	13.10