



Compact structure ,small size.

Multi-functional wire controllor.

Various power optional.

Parameters:

Model [Ⓞ]	CJB200B [Ⓞ]		CJB300B [Ⓞ]		CJB400B [Ⓞ]		CJB600B [Ⓞ]	
Working Voltage [Ⓞ]	DC12V [Ⓞ]	DV24V [Ⓞ]	DV12V [Ⓞ]	DV24V [Ⓞ]	DV12V [Ⓞ]	DV24V [Ⓞ]	DV12V [Ⓞ]	DV24V [Ⓞ]
Working Current [Ⓞ]	8±1A [Ⓞ]	4±1A [Ⓞ]	11.5±1A [Ⓞ]	6±1A [Ⓞ]	8±1A [Ⓞ]	4±1A [Ⓞ]	11.5 ± 1A [Ⓞ]	6±1A [Ⓞ]
Idle current [Ⓞ]	≤1A [Ⓞ]	< 500mA [Ⓞ]	≤1A [Ⓞ]	< 500mA [Ⓞ]	≤1A [Ⓞ]	< 500mA [Ⓞ]	≤1A [Ⓞ]	500mA [Ⓞ]
Quiescent current [Ⓞ]	≤ 350mA [Ⓞ]	< 200mA [Ⓞ]	≤350mA [Ⓞ]	< 200mA [Ⓞ]	≤ 350mA [Ⓞ]	< 200mA [Ⓞ]	≤ 350mA [Ⓞ]	< 200mA [Ⓞ]
Load impedance [Ⓞ]	8Ω [Ⓞ]		6Ω [Ⓞ]		8Ω [Ⓞ]		6Ω [Ⓞ]	
Matched Speaker [Ⓞ]	2x100W [Ⓞ]		2X150W [Ⓞ]		2X100W [Ⓞ]		2X150W [Ⓞ]	
Tones	Wail-1,Wail-2,Hi-Lo, Yelp, Traffic, Tool,Air Horn,Siren [Ⓞ]							
Light control [Ⓞ]	Three ways [Ⓞ]							