



Rugged-Reliable Two-way Radio





Compact & Fashionable Design

- Power Output: 5W
- Compact and Fashionable Design
- Double Color Injection Technology
- Built-in Large Scale Integrated Circuit
- High Audio Output, Superb Clear Audio Quality




Handheld Two-way Radio

http://www.sfecom.cn

Main Features

- 16 Channels
- Power Output 5W
- Built in CTCSS and DCS
- PC Programming
- Auto Battery Save
- Emergency Alert
- Voice Guide
- VOX Function
- Time Out Time(TOT)
- Busy Channel Lockout
- High/low Power Selective
- Auto-scan and Priority Scan
- Large Li-lon Battery 1300mAh
- Built-in Large Scale Integrated Circuit
- Wide/Narrow Bandwidth Selective
- Superb Clear and Strong Audio Quality



General	
Frequency Range	UHF: 400-470MHz VHF: 136-174MHz
Channel Capacity	16CH
Channel Spacing	25/12.5KHz
Operating Voltage	7.4V DC ± 20%
Antenna Impedance	50Ω
Dimension (Antenna Excluded)	55x28x105mm
Weight(Antenna & Battery Included)	7.4V about 215g
Transmitter	
Frequency Error	≤ 5 X 10 ⁻⁶
RF Power Output	≤ 5W
Modulation Limiting	≤ 5KHz
Modulation Distortion	Less than 5%
Spurious Emission	≥ 65dB
Receiver	
Sensitivity	12dB SINAD(0.18µV)
Adiacent Channel Selectivity	≥ 55dB

e e nom ny	
Adjacent Channel Selectivity	≥ 55dB
Spurious Response Rejection	≥ 55dB
Intermodulation	≥ 55dB
Audio Distortion	≤ 5%
Audio Output	≥ 250mW

Above specifications are tested according to TIA/EIA-603.

Above specifications are subject to change without any notice due to technology enhancement.

••• Quanzhou SFE Electronic Technology Co.,Ltd Address:Daping Industry Park, Fengze District, Quanzhou City, Fujian Province, China 362000

SFE retains the right to change the product design and specifications without notices. If any printing mistake occurs, SFE will not bear any relevant responsibility.

© 2013 SFE Electronic Technology Co.,Ltd.All Rights Reserved.

Your Local Dealer