

KYD®

NC-500/600A

Specifications

Model	NC-500A	NC-600A
Frequency Range	VHF 136-174MHz	UHF 400-430MHz 430-480MHz
Channel Capacity	16	
PLL Channel Spacing	12.5/25KHz	
Battery Voltage	7.4V DC (Li-Ion Battery Pack)	
Antenna Impedance	50Ω	
Operating Temperature	-20°C ~ +60°C	
Frequency Stability	± 2.5PPM	
Dimensions (With Battery)	110(H)X55(W)X34(D)mm	
Weight (With Battery)	250g	
Standard Package	Radio with Standard Accessories	

Compatible With American Military Standard[MIL-STD-810C/D/E]

Standard Accessories:



Product Picture:



Features:

- ◆ 107 DCS
- ◆ 50 CTCSS
- ◆ Wired Clone
- ◆ Hi/Low Power
- ◆ Voice Announcement
- ◆ Time-out Timer
- ◆ Low Battery Alert
- ◆ PC Programmable
- ◆ Selectable Squelch Level
- ◆ CO/TO/SE Scan Switchable
- ◆ Priority Scan
- ◆ Channel Scan
- ◆ Li-ion Battery Pack
- ◆ Busy Channel Lockout

Transmitter (Measurements made per TIA/EIA-603)

RF Power Output	4/5W
Modulation Type	F3E
Maximum Deviation	< ± 5.0KHz
Spurious Emission	< 65dB Below Carrier
Modulation Distortion	< 5%(300-3000Hz)
FM Noise	< -45dB

Sensitivity(12dB SINAD)	0.2 μV
Squelch Selectivity	0.15 μV
Adjacent Channel Selectivity	> 65dB
Intermodulation	> 65dB
Spurious Rejection	> 60dB
Image Rejection	> 65dB
FM Harm And Noise	< -45dB
Modulation Type	16KOF3E
Operating Bandwidth	< ± 7KHz
AF Output @ 4 Ohms	0.5W
Audio Distortion	< 5%

Receiver (Measurements made per TIA/EIA-603)

Circuit Type	Double-conversion Superhetrodyne
IFs	38.850MHz & 450KHz



China New Century (Quanzhou) Communication Electronics Co.,Ltd

ADD: NO.1 FENGSHOU ROAD, ZHAOFENG INDUSTRIAL DISTRICT, QUANZHOU CITY, FUJIAN PROVINCE, CHINA.

TEL: (86)595-22899399 22883777 22882777

FAX: (86)595-22887666

E-mail: fjqzgw@pub2.qz.fj.cn Http: // www.century-comm.com