

Thermal POS printer series

Model: RP803

80mm thermal POS printer



Specification:

Printing Method	Thermal line printing
Printing Speed	250mm/s
Resolution	8mm/s,576 dots/line
Character Set	ANK character,GB18030(Chinese) Font A:12*24dots, Font B:9*17dots, Jan/traditional form:24*24dots
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/ CODABAR/ITF/CODE39/CODE93/CODE128
Interface	USB/USB+Bluetooth/USB+WIFI
Power	DC 24V/2.5A
Cashbox control	DC 12V-24V/1A
Reliability (MCBF)	150km
Work environment	Temperature: 0~45°C; Dampness:10~80%
Storage environment	Temperature: -10~60°C; Dampness:10~90%
Paper Width	79.5± 0.5mm
Max diameter of paper roll	80mm
Paper thickness	0.06~0.08mm
Weight	1.3kg (N.W.) 2.80kg(G.W.)
Dimension	195Lx148Wx145H mm
Drivers:	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP /Win Vista/Windows 7/Linux/OPOS
Auto-cutter	All cut or partly cut as optional
Printing command	Compatible with POS/ESC command set
Line spacing	3.75mm(can be adjusted by command)

Feature

- ★ Variety of exterior casing color(red, beige,silver,ebony black, computer white)
- ★ High speed、high life、high quality、low repair rate, apply to all sorts of business software
- ★ Increase lose sales avoiding function to avoid the situation of losing order, practically guarantee user's vital interests
- ★ All cut or partly cut as optional
- ★ Support download Logo printing
- ★ Standard GB18030 Chinese character
- ★ Support simplified & traditional Chinese, and multiple international language
- ★ 100MB Ethernet interface connection, print more quickly, avoid losing sales.

Application:

- ◆ Telecommunications
- ◆ Logistics
- ◆ Bank
- ◆ Market
- ◆ Monopoly store
- ◆ Catering
- ◆ Hotel
- ◆ Tax Administration
- ◆ Executive branch