

ENGINE	
Emission Regulation	Tier 2 / Stage II
Make	Cummins
Model	6LTAA9.3
Gross Power	162 kW (220 hp) @ 2,200 rpm
Net Power	148 kW (201 hp) @ 2,200 rpm
Peak Torque	890 N · m
Displacement	9.3 L
Number of Cylinders	6
Aspiration	Turbocharged & Air-to-air intercooled

TRANSMISSION	
Transmission Type	Countershaft, power shift
Torque Converter	Single stage, three elements
Maximum Travel Speed, fwd	37 km/h
Maximum Travel Speed, rev	24 km/h
Number of Speeds, fwd	4
Number of Speeds, rev	3

AXLES	
Differential Front Type	Limited slip
Differential Rear Type	Limited slip
Axle Oscillation	±11°

STEERING	
Steering Configuration	Articulated
Steering Relief Pressure	16 MPa

BRAKES	
Service Brake Type	Wet discs brake
Service Brake Actuation	Hydraulic
Parking Brake Type	Manual electronic control
Parking Brake Actuation	Hydraulic

HYDRAULIC SYSTEM	
Main Pump Type	Gear
Main Relief Pressure	20 MPa
Raise	6 s
Dump Time	1.5 s
Float Down Time	3 s
Fastest Total Cycle Time	10.5 s

LOADER ARM PERFORMANCE	
Tipping Load - Straight	12,500 kg
Tipping Load - Full Turn	10,500 kg
Bucket Breakout Force	160 kN
Maximum Dump Angle at Full Height	45°
Dump Clearance at Full Height Discharge	3,100 mm
Dump Reach at Full Height Discharge	1,035 mm
Maximum Hinge Pin Height	4,154mm
Maximum Digging Depth, Bucket Level	61 mm
Bucket Rollback at Ground Level	42°
Bucket Rollback at Carry	46°
Bucket Rollback at Maximum Height	59°

BUCKET PERFORMANCE	
Reference Bucket	3 m³

DIMENSIONS	
Length with Bucket Down	8,150 mm
Width Over Tires	2,750 mm
Wheelbase	3,250 mm
Wheel Tread	2,150 mm
Ground Clearance	431 mm
Turn Angle, Either Side	38°
Rear Angle of Departure	30°
Turning Radius, Outside of Tire	6,095 mm
Turning Radius, Center of Tire	5,795 mm
Turning Radius, Bucket Carry	6,775 mm

TIRES	
Tire Size	23.5 - 25

OPERATING WEIGHTS	
Operating Weight	17,000 kg

SERVICE CAPACITY	
Fuel Tank	320 L
Engine Oil	19 L
Cooling System	52 L
Hydraulic Reservoir	218 L
Transmission and Torque Converter	45 L
Axles, each	32 L