

Technical Data for CPD30 Forklift

Speciality parameter	型号 Model			Unit	CPD30	
	动力形式 Power type				蓄电池 Battery	
	额定起重量 Rated capacity			kg	3000	
	载荷中心距 Load center		d	mm	500	
	标准起升高度 Lift height		h2	mm	3000	
	门架倾角(前/后) Mast tilt angle (forward/backward)		α/β	Deg	6/8	
	轴距 Wheel-base		L4	mm	1700	
	轮距(前/后) Tread(front/rear)		b4/b5	mm	1000/980	
Performance parameter	起升速度(满载) Lift speed(with load)			mm/s	250	
	行驶速度(满载) Travel speed (with load)			km/h	14	
	最大爬坡(满载) Max. gradeability (with load)			%	15	
Power, transmission and others	电机 Motor	牵引电机 Driving Motor	额定功率 Rated power	kw	16.6	
		工作电机 Working Motor	额定功率 Rated power	kw	12	
	控制器 Controller	制造商 Manufacturer			CURTIS	
	蓄电池 Battery	电压 Voltage			V	80
		容量 Capacity			Ah	560
	轮胎 Tire	前 Front	类型 Type			空心胎 Penumatic tire
			型号 Model			28x9-15-12PR
		后 Rear	类型 Type			
型号 Model						18x7-8

Others	自重Dead weight			kg	4950	
	自由起升高度Free lift height		h4	mm	135	
	货叉Fork	厚度×宽度×长度 Thickness×Width×Length	c×b×a	mm	40×122×1150	
	外形尺寸 Overall dimensions	全长（不带货叉） Overall length(without forks)		L2	mm	2530
		全宽Overall width		b1	mm	1225
		全高 overall height	门架升起时 extended height(mast)	h1	mm	4040
			门架未升起Lower height(mast)	h3	mm	2080
	护顶架Overhead guard		h7	mm	2100	
最小转弯半径Min. turning radius		Wa	mm	2180		
最小离地间隙Min. under ground clearance		m1	mm	114		