

(NS1938) VGA -Video Converter Box

Features

The whole family shares one computer, watching movies and playing games on the internet.

The popularization of computers brings great conveniences for people's work and life. Maybe at one certain occasion you need to change the VGA signals into Video/S video signals. The movies you downloaded from the internet can be entirely combined to the family cinema, and you can easily experience cinema effect ion. You also can demonstrate the BRM need to be presented to the audience through the large-screen TV,

Video Converter can easily help you to realize the conversion of VGA signals into Video/S video signals.



Product Specification

Based on widely successful scan converters, the PI2000 pushes the performance threshold of high quality images at high resolution with added flexibility and functionality at an affordable price.

Performance Parameter

◆One input of VGA signals, one output of VGA signals,

◆One output of Video, one out put of S Video,

◆One ACPI of 5V

◆Resolutions of

VGA signals:640x480@60/72/75/85Hz, 800x600@60/75Hz, 1024x768@60/75Hz; [1280x1024@60Hz](#)

◆At the same time, output the VGA\VIDEO\S-VIDEO signals.

◆Show Simultaneous pictures on the monitor and TV

◆Support the systems below :

The TV systems of NTSC (Taiwan and USA), NTSC-EIAJ (Japan), PAL (EURO, China)

PAL-M (Brazil), PAL-N(Uruguay Paraguay)

◆Support the OVERSCAN and UNDERSCAN display mode,

◆Convenient to carry because it is light, thin ,short and small

◆Volume: 110mm(length)x56mm(width)x36mm(height)

Connect

