SHENZHEN CHINARY CO., LTD.

Rm.1804, Wensheng Center, Wenjin Plaza, 1010 Wenjin Road (N), Shenzhen 518020, China Tel: +86 755 2563 1576, 2563 1639 Fax: +86 755 2560 0566, 2562 5060

E-mail: info@chinary.com.cn Http://www.chinary.com.cn

LWC For ACR SERIES (PLAIN)

Specifications			Thickness							
			0.016"	0.02"	0.024"	0.028"	0.032"	0.04"	0.048"	0.06"
			0.41mm	0.5mm	0.61mm	0.71mm	0.81mm	1.02mm	1.22mm	1.5mm
O.D.	<0.1575 "	4mm		√						
	<0.2 (1/5)"	5mm	√	√	√	√	√	√		
	<0.25 (1/4)"	6.35mm	√	√	√	√	√	√		
	<0.315 "	8mm	√	√	√	√	√	\checkmark	√	√
	<0.375 (3/8)"	9.52mm	√	√	√	√	√	√	√	√
	<0.50 (1/2)"	12.7mm		√	√	√	√	√	√	√
	<0.55"	14mm			√	√	√	√		
	<0.625 (5/8)"	15.88mm			√	√	√	√	√	
	<0.75 (3/4)"	19.05mm				√	√	√	√	
	<0.875 (7/8)"	22.22mm					√	√		
Remarks			 Tubes with marks √ are supplied Standard: ASTM B-280 (GB/T-17791) Materials: C1100(T2), C10200 (TU2), 12200 (TP2) Outer diameter: 3.18 ~ 28.58mm (1/8" ~ 1 1/8") Thickness: 0.36 ~ 1.50mm (0.014" ~ 0.059") Length: ≤ 30.48m (100 ft) If you will have any special requirements about specifications, please contact us so as to meet the demands 							
Packing			 With plastic cap to protect both ends Standard export packages Custom suffocating free 							