

<b>Specification</b>	Nominal Input Voltage	100-240VAC(Full Range), 50/60Hz	
<b>Input</b>	Input Voltage Range	90-264VAC(Full Range), 47/63Hz	
	Input current(rms)	0.15A max/90VAC	
	surge current	30 Amps Max. Cold start at 240Vac input, with rated load and 25°C ambient.	
	Withstanding voltage	3.3kV, 1 minute, 5mA (maximum),between primary and secondary	
	Iusulation resistance	Primary to secondary:10MΩ min at 500V DC	
	EMI		FCC Class B
			CISRP22 Class B
		EN55024 Class B	
<b>Output</b>	Maxinum power(Po)	5W max	
	Voltage(Vo)	DC4-12V	
	Output current	0.1A-1A	
	Voltage regulation	±5%@constant volatage mode	
	Ripple and noise	150mV max	
	Efficiency	Compliant CEC efficiency level V and Erp Stage II	
	Quality test	100% quality test and aging test	
	Protection		OVP, AC recycle, OCP,SCP,OTP
		Short circuit protection	
<b>Dropping Packed</b>	1 corner,3 edges, and 6 surfaces		
<b>Safety</b>	EMI, FCC, CE, EMC& LVD, EN60950, UL60950, J60950, AS/NZS60950-1, GB4943-2001		
<b>Environmental</b>	Humidity	Operating: 10 to 95% RH	
		Storage: 10 to 95% RH	
	Operation temperature	0° C to 40° C ambient	
	Storage temperature	, -20°Cto +70°C	
	MTBF: > 20, 000 hours at full load and 25° C ambient temperature		
<b>Size</b>	UL:L*W*H=59.2*25*42.5mm , VDE:L*W*H=59.2*25*42.5mm , BS:L*W*H=59.2*48.5*49.8mm , SAA:L*W*H=59.2*41.5*50mm		
<b>Packaging</b>	PE bag or carton box		