

No. of cores and mm2 per conductor N×mm2	Approx. outside diameter mm	Copper Weight kg/km	Approx. weight of cable kg/km	No. of cores and mm2 per conductor N×mm2	Approx. outside diameter mm	Copper Weight kg/km	Approx. weight of cable kg/km
2×0.5	7.1	41.0	69.0	3×2.5	11.8	146.0	211.0
3×0.5	7.3	45.5	77.0	4×2.5	13.5	167.0	310.0
4×0.5	7.9	55.0	93.0	5×2.5	14.6	200.0	326.0
5×0.5	8.4	66.0	106.0	7×2.5	15.9	288.0	443.0
7×0.5	8.9	80.5	126.0	4×4	15.1	237.0	401.0
2×0.75	7.4	45.0	80.0	5×4	16.5	328.0	478.0
3×0.75	7.9	57.9	92.0	4×6	16.6	318.0	522.0
4×0.75	8.4	64.0	109.0	5×6	18.2	440.0	621.0
5×0.75	8.9	77.4	124.0	4×10	21.1	558.0	843.0
7×0.75	9.7	102.0	155.0	5×10	23.1	714.0	1004.0
2×1.0	7.9	50.0	92.0	4×16	23.9	804.0	1395.0
3×1.0	8.2	65.3	105.0	5×16	26.8	1050.0	1812.0
4×1.0	8.7	78.1	124.0	4×25	29.4	1289.0	1903.0
5×1.0	9.5	89.4	147.0	5×25	32.6	1446.0	2374.0
7×1.0	10.2	114.0	178.0	4×35	32.4	1693.0	2489.0
2×1.5	9.9	77.0	126.0	5×35	36.0	1975.0	2771.0
3×1.5	10.3	83.0	164.0	4×50	38.8	2342.0	3362.0
4×1.5	11.3	100.0	198.0	4×70	43.7	3035.0	3719.0
5×1.5	12.6	125.0	240.0	4×95	50.4	4055.0	5849.0
7×1.5	13.9	196.0	314.0	4×120	56.8	5225.0	7509.0