

CQD系列站驾式前移式电动叉车

CQD SERIES STANDING TYPE REACH TRUCK

主要特点 MAIN CHARACTER

1. 美国CURTIS交流控制器，质量可靠，性能优异，使整车性能达到最佳状态
 2. WINNER液压站，低噪音，小振动，密封性能好，确保起升下降平稳可靠
 3. 交流驱动电机，免维护，提供强大动力，具有更强的满载爬坡能力
 4. 高强度车身设计，特殊压制工艺制造的“C”型钢门架，坚固耐用，使用寿命长
 5. 两用立式驱动，使电机、刹车等的检测、维修直接方便
 6. 配置大容量牵引电池，电量持久，并选用智能充电器，德国REMA充电插件，充电方便快捷
 7. EPS电动转向系统，转向轻便
 8. 可选配折叠式踏板，具有减震功能，可消除操作者在行驶过程中路面给予的冲击
 9. 可选配人性化的护臂结构，并闭操作方便，并具备较强的抗撞击力，真正起到护臂作用
1. Top quality AC controller system from CURTIS, high reliability, ensures best performance in different states
 2. WINNER hydraulic power pack, low noise, few vibration and excellent leak tightness, ensures smooth lifting
 3. AC traveling motor, maintenance-free, provides stronger power and climbing capability
 4. High-strength frame design and "C" shaped mast, strong and durable, ensures longer service life
 5. Vertical motor designing, ensures inspection and maintenance of motor and brake system conveniently
 6. Configure with 240Ah large capacity battery, intelligent charger, REMA plug from Germany
 7. EPS electric power steering system, turning lightly
 8. Optional folded pedal, with buffering function, avoid shake while traveling
 9. Optional humanized design of handrail, protect the operator when operating





AZ10/AZ13/AZ15

AZ10/AZ13/AZ15



1. 美国CURTIS控制器
 2. 交流立式驱动，带电转向
 3. WINNER液压站
 4. 德国REMA充电插件
 5. 操板杆控制货叉和门架的移动，操作方便
 6. 门架前后移动功能
 7. 货叉前后仰功能
 8. 人性化设计的操作手柄，带紧急反向行驶按钮
 9. 紧急情况下可按下红色断电开关，切断所有电源，车子立即停止
1. CURTIS controller from America
 2. Vertical AC traveling and steering motor, maintenance conveniently
 3. WINNER pump station from Taiwan
 4. REMA plug from Germany
 5. The levers control moves of forklifts and mast, easy operation
 6. Mast can move forward and backward
 7. Forks can tilt forward and backward
 8. Humanized design of handle, with red reverse button
 9. Press the red button in an emergency, cut down all the power, stop the truck



技术参数 TECHNICAL DATA

		CQD10				
特性 Identification	产品型号 Model	AZ10		AZ13/AZ15		
	配置号 Config-code	无踏板 Without pedal	AZ10	AZ13/AZ15	AZ13/AZ15	
基本尺寸 Dimension	驱动形式 Drive Unit	带踏板 With pedal	电动 Electric			
	驾姿方式 Operation type		步行式Pedestrian / 站驾式Standing			
	额定载重 Load capacity	Q kg	1000	500	1300/1500	
	载荷中心 Load center	C mm				
	总长 Overall length	L mm	1900	2015		
	总宽 Overall width	b mm	1000	1080		
	总高 Overall height	H2 mm	1840	2090	1840	2090
	前移距离 Reach length	L2 mm		550		
	起升高度 Lift height	H1 mm	2500	3000	2500	3000
	作业时最大高度 Max working height	H1 mm	3431	3931	3431	3931
电机 Electric Motor	自由提升高度 Free lift height	H3 mm	200			
	货叉尺寸 Fork dimensions	L1 x b2 x m mm	1000x100x35			
	货叉外宽 Maximum fork width	b1 mm	200-670可调(Adjustable)			
	货叉倾角 Fork obliquity	α/β °	3/5			
	最小离地间隙 Minimum ground clearance	m1 mm	60			
	转弯半径 Turning radius	Wa mm	1485	1600		
重量 Weight	驱动电机功率 Drive motor power	KW	2.0			
	提升电机功率 Lift motor power	KW	2.0			
	转向电机功率 Steering motor power	KW	0.2			
	蓄电池 Battery	Ah/V	240/24			
重量 Weight	净重(不含电池)Weight w/o battery	kg	1201	1251	1308/1418	
	电池重量 Battery weight	kg	235			