

Rm.1804, Wensheng Center, Wenjin Plaza, 1010 Wenjin Road (N), Shenzhen 518020, China
Tel: +86 755 2563 1576, 2563 1639 Fax: +86 755 2560 0566, 2562 5060
E-mail: info@chinary.com.cn
[Http: //www.chinary.com.cn](http://www.chinary.com.cn)

Copper Alloy Tube

Specifications		Thickness (mm)											Length (mm)
		0.4	0.4-1	1-2	2-3	3-4	4-5	5-6	6-7	7-8	8-10	10-12	≤25000
O.D. (mm)	6.35-10	√	√										≤25000
	>10-20	√	√	√	√	√							≤25000
	>20-50		√	√	√	√	√	√	√				≤25000
	>50-100			√	√	√	√	√	√	√	√	√	≤15000
	>100-133				√	√	√	√	√	√	√	√	≤6000
Remarks		○ Mraks with √ are supplied ○ Standard: ASTM B111 (GB/T-1527) ○ Materials: C44300(HSn70-1). C68700Hal77-2). C70600(BFe10-1-1) .C26000(H70). C33000(HPb66-0.5) etc. ○ Outside diameter: 6.35 to 133mm ○ Thickness: 0.4 to 12mm ○ Length: 6000 to 25000mm											
Packing		○ With plastic cap to protect both ends ○ Plastic bag wrapped outside pipe ○ Pack with wooden box ○ As requirements											