

## **SP-POS58III Specification**

### **Features:**

**Low noise thermal printing**  
**Versatile and adaptable**  
**Different models for option**  
**Paper end sensors are available**  
**Easy to use and simple to maintain**  
**Easy paper loading for paper replacement**  
**Support printing graphics and barcode**

### **Specifications:**

**Printing method: thermal line**  
**Printing speed: 70mm/s or 20lines/s**  
**Resolution: 8 dots/mm, 384 dots/line**  
**Effective printing width: 48mm**  
**Character set: IBM character set II, GB2312-80(Chinese)**  
**Print font: ANK: 12 x 24 Chinese: 24 x 24**  
**Character per line: 32**  
**Paper type: thermal paper**  
**Paper width: 57.5#177;0.5mm**  
**Paper roll diameter:**  
**Maximum: 83.0mm**  
**Roll core inner diameter: 13mm(minutes)**  
**Paper thickness: 0.06 to 0.07mm**  
**Paper supply method: drop-in paper load**  
**MCBF(MCBF)**  
**Mean cycles between failure: 5 million lines**  
**Auto cutter: N/A**  
**TPH: 100km**  
**Barcodes: UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128**  
**Emulation: ESC/POS**  
**Driver: Windows98/2000/NT/XP**  
**Sensor: paper end sensor**

**Drawer port: 1 Port**

**Interface: RS-232, parallel, USB, Ethernet**

**Power supply(adapter): AC100 to 240V &#177; 10%(include) DC 12V, 3A**

**Auto cutter life : N/A**

**Cutting method: N/A**

**Net weight: 800g**

**Gross weight: 1.8kg**

**Gross weight for shipment(12 pieces/carton): 16.5kg**

**Printer dimension(W x L x H): 138 x 216 x 125mm**

**Package dimension(1 piece)(W x L x H): 270 x 260 x 165mm**

**Shipment dimension(12 pieces/carton)(W x L x H): 560 x 560 x 350mm**

**Color: beige**

**Operating temperature: 0 to 50 degrees C**

**Storage temperature: -20 to 60 degrees C**

**Operating humidity: 10 to 80%**

**Storage humidity: 10 to 90%**

**Applications: restaurants, department stores, kitchen, convenience stores, specialty retail, supermarket**