

No. of cores and mm2 per conductor N×mm2	Approx. outside diameter mm	Copper Weight kg/km	Approx. weight of cable kg/km	No. of cores and mm2 per conductor N×mm2	Approx. outside diameter mm	Copper Weight kg/km	Approx. weight of cable kg/km
2×0.75	5.4	12.9	50.1	4G1.5	7.2	49.7	106.1
3G0.75	5.7	19.3	59.5	5G1.5	8.1	62.1	133.1
4G0.75	6.2	25.7	71.4	7G1.5	8.9	87.0	171.9
5G0.75	6.7	32.2	86.1	8G1.5	10.0	99.4	218.7
7G0.75	7.3	50.4	104.3	9G1.5	10.7	111.4	256.2
10G0.75	9.6	64.3	156.2	12G1.5	11.4	149.2	285.2
12G0.75	9.9	77.2	178.6	14G1.5	12.6	174.0	329.9
15G0.75	11.1	108.0	231.1	18G1.5	14.4	223.7	429.5
16G0.75	11.1	115.2	231.1	21G1.5	15.7	261.0	479.4
18G0.75	11.7	129.6	254.3	25G1.5	16.9	310.7	560.1
21G0.75	13.0	135.0	301.6	3G2.5	8.1	62.1	135.6
25G0.75	13.8	160.8	351.4	4G2.5	8.9	82.9	166.2
41G0.75	17.3	295.2	560	5G2.5	10.0	103.6	208
2×1	5.7	17.1	58.4	7G2.5	11.1	145.0	269
3G1	6.0	25.7	70	12G2.5	14.8	248.0	438.8
4G1	6.5	34.3	84.7	18G2.5	17.8	372.9	661.3
5G1	7.2	42.9	101.8	3G4	9.9	115.2	201
7G1	8.0	60.0	132.3	4G4	10.8	153.6	249
12G1	10.5	102.9	214.8	3G6	11.8	172.8	289
16G1	11.8	137.2	272.8	4G6	13.0	230.4	365
18G1	12.7	154.3	303.7	4G10	16.1	384.0	590
25G1	14.7	214.3	410	4G16	18.9	614.4	1087
2×1.5	6.3	24.9	71.5	4G25	23.5	960.0	1582
3G1.5	6.7	37.3	87				