



SHANGHAI UPG INTERNATIONAL TRADING CO., LTD



LQMT Series Automatic Flute Laminator

Add: Room 2403 Jincheng Mansion 511 Tianmuxi Road, 200070 P.R.China

TEL: 86-21-63177436 FAX: 86-21-63538343

Email: huangwei@shanghai-upg.com



LQMT Series Automatic Flute Laminator

1. Quotation:

| | |
|-----------|----------|
| LQMT-1300 | USD/unit |
| LQMT-1450 | USD/unit |
| LQMT-1600 | USD/unit |

2. Terms of Payment:

- 30% deposit by T/T when confirming the order
- 70% balance by T/T before shipping.

3. Performance of the machine:

- 1) LQMT Series Automatic Flute Laminator adopts chain pusher and back registration system together with spring blade side lay and vacuum sucking conveying system makes this series of machine fit for a larger range of paper, high precision while remaining the features of easy operation and maintenance.
- 2) The core designed rubber roller together with knurled steel roller enhances the evenness of gluing, strength of stickiness, as well as lowering the production cost.
- 3) Balance-tested rollers, tight assembling technique, plus timing and tooth belt driving mechanic system makes the machine run at low noise with high precision.
- 4) The machine adopts automatic glue supply and recyclable glue circulating system.
- 5) Self-developed high-strength feeder compliant with high configuration electric system makes the machine run at low malfunction and stable. The electric parts used are all world wide available brand or well-known Chinese brand.
- 6) All material are inspected according to ISO-9001 standard and the key parts such as the harmonic gear and bearings are imported ones.
- 7) The bottom sheet for this machine can be A, B, C, D, E, F flute corrugated sheet. It can do 3 or 5 ply board to sheet lamination or board to board lamination. The range for top paper can be 200-600 GSM with top paper advance or alignment function.

4. Specifications:

| Model | LQMT-1300 | LQMT-1450 | LQMT-1600 |
|--------------------|--------------|--------------|--------------|
| Maximum size | 1300×1100mm | 1450×1100mm | 1600×1400mm |
| Minimum size | 350×350mm | 350×350mm | 380×350mm |
| Laminate precision | ≤±1.5mm | ≤±1.5mm | ≤±1.5mm |
| Speed | 6000Sheets/h | 6000Sheets/h | 6000Sheets/h |
| Total power | 11.65kw | 11.65kw | 15.3kw |
| Length | 12.5m | 12.5m | 15m |
| Total weight | 6.8T | 7.2T | 8.0T |