











Goldensun LED Panel Lights Catalog--2

Model	Power	Picture		Parameter	Color Temperatur	Carton Measurement & PCS/CTN	
GT3030-18W	18W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency \geq 80lm/W ; Ra \geq 80 ; PF $>$ 0.9 Engineering Size : 300*300*H40mm N.W : 1.2KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	62*62*26 cm	10pcs/ctn
GT4040-32W	32W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency \geq 80lm/W ; Ra \geq 80 ; PF $>$ 0.9 Engineering Size : 400*400*H40mm N.W : 1.68KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	84*84*26 cm	5 pcs/ctn
GT3060-24W	24W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency \geq 80lm/W ; Ra \geq 80 ; PF $>$ 0.9 Engineering Size : 300*600*H40mm N.W : 1.4KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	34*64*26 cm	5 pcs/ctn
GT3090-36W	36W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency \geq 80lm/W ; Ra \geq 80 ; PF $>$ 0.9 Engineering Size : 300*900*H40mm N.W : 2.25KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	92*32*26 cm	10pcs/ctn
GT30120-48W	48W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency \geq 80lm/W ; Ra \geq 80 ; PF $>$ 0.9 Engineering Size : 300*1200*H40mm N.W : 3.5KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	31*122*26 cm	5 pcs/ctn

GT5050-36W	36W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency≥80lm/W ; Ra≥80 ; PF>0.9 Engineering Size : 500*500*H40mm N.W : 0.84KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	52*52*26 cm	5 pcs/ctn
GT6060-36W	36W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency≥80lm/W ; Ra≥80 ; PF>0.9 Engineering Size : 600*600*H40mm N.W : 0.84KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	64*64*26 cm	5 pcs/ctn
GT6060-48W	48W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz Parameter: Luminous Efficiency≥80lm/W ; Ra≥80 ; PF>0.9 Engineering Size : 600*600*H40mm N.W : 0.84KG Sanan LED Chip , PS Nanometer LGP Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	64*64*26 cm	5 pcs/ctn