



# WinFull Technology Co., Ltd.

1F., No.3, Ln. 46, Lishan St., Neihu Dist., Taipei City 11449, Taiwan.

T: +886 2 2627 1758 F: +886 2 2627 1795 E-Mail: [sales@winfulltek.com.tw](mailto:sales@winfulltek.com.tw)

## Detailed description and technical specifications

Item No	BK450	BK650	BK850	BK1000B
Capacity	450VA/240W	650VA/360W	850VA/480W	1000VA/600W
INPUT				
Voltage	110/120 VAC or 220/230/240 VAC			
Voltage Range	81-145VAC or 140-300VAC			
Frequency Range	60/50 Hz (Auto sensing)			
OUTPUT Voltage	110/120 VAC or 220/230/240 VAC			
AC Voltage Regulation (Bat Mode)	±10%			
Frequency Range (Bat Mode)	60Hz or 50Hz ± 1Hz			
Transfer time	Typical 2-6ms			
Waveform (Bat Mode)	Simulated Sinewave			
Battery				
Battery Type&Number	12V 4.5Ah*1	12V 7Ah*1	12V 9Ah*1	12V 9Ah*1
Floating Charging Voltage	13.7VDC			
Charging ability	4-6 hours recover to 90% capacity			
Protection				
Full protection	Overload, discharge, and overcharger protection			
Indications				
Line mode	Green lighting			
Battery mode	Yellow flashing			
Fault	Red lighting			
Alarm				
Battery mode	Sounding every 10 seconds			
Low battery	Sounding every second			
Overload	Sounding every 0.5 seconds			
Battery Replacement Alarm	Sounding every 2 seconds			
Fault	Continuously sounding			
Dimension, D*W*H(mm)	279*101*142			
Net Weight (kgs)	3.5	4.2	4.9	4.9
Environment				
Humidity	0-90% Relative Humidity 0-40 °C (Non-condensing)			
Noisy Level	Less than 40dB			
Remarks				
Minimum Quantity	1000PCS			
Sample Lead time	2 or 3 days			
Customed Printing	1 color logo free			
Delivery Lead Time	22 Days			
Payment Terms	TT in advance			
Master packing weight	GW: 4.2KGS			
<b>Container quantity</b>				
			1X20'	1X40'
			1800	3600

