

No. of cores and mm2 per conductor N×mm2	Approx. outside diameter mm	Copper Weight kg/km	Approx. weight of cable kg/km		No. of cores and mm2 per conductor N×mm2	Approx. outside diameter mm	Copper Weight kg/km	Approx. weight of cable kg/km
2×0.14	3.9	12.0	20.0		15×0.25	8.3	61.0	111.0
3×0.14	4.1	13.0	28.0		16×0.25	8.4	64.0	124.0
4×0.14	4.3	14.3	33.0		18×0.25	8.8	83.0	143.0
5×0.14	4.6	15.5	38.0		20×0.25	9.3	88.0	152.3
7×0.14	4.9	18.2	38.0		21×0.25	9.6	93.0	161.0
6×0.14	4.9	19.0	49.0		25×0.25	10.7	114.0	172.0
8×0.14	5.8	21.2	56.0		28×0.25	10.8	126.0	181.1
10×0.14	6.1	28.5	66.0		30×0.25	11.0	132.0	189.0
12×0.14	6.3	30.4	78.0		32×0.25	11.4	138.0	203.0
14×0.14	6.7	32.0	80.0		36×0.25	11.8	148.0	220.0
15×0.14	6.9	37.8	86.0		2×0.34	4.9	21.0	37.0
16×0.14	7.0	43.0	90.0		3×0.34	5.1	27.0	49.0
18×0.14	7.3	48.8	104.0		4×0.34	5.7	28.0	59.0
20×0.14	7.7	53.9	116.0		5×0.34	6.2	30.0	66.0
21×0.14	7.9	55.5	121.0		6×0.34	6.8	45.0	79.0
25×0.14	8.4	63.0	149.0		7×0.34	6.8	48.0	83.0
28×0.14	8.5	66.1	153.0		8×0.34	7.8	52.0	94.0
30×0.14	8.7	69.0	158.0		10×0.34	8.3	74.0	129.2
32×0.14	9.0	73.6	164.0		12×0.34	8.5	80.0	142.2
36×0.14	9.3	83.0	183.0		14×0.34	8.9	86.0	154.0
2×0.25	4.5	16.0	32.0		15×0.34	9.2	90.0	155.0
3×0.25	4.7	21.0	37.0		16×0.34	9.4	94.0	160.0
4×0.25	5.0	24.0	41.3		18×0.34	10.2	103.0	173.0
5×0.25	5.6	29.0	51.2		20×0.34	10.7	112.0	192.0
6×0.25	6.0	30.0	58.0		21×0.34	11.1	116.0	199.2
7×0.25	6.0	37.0	65.0		25×0.34	11.9	135.0	259.0
8×0.25	7.1	42.0	73.0		28×0.34	12.0	153.0	280.0
10×0.25	7.5	46.0	82.0		30×0.34	12.3	159.0	291.1
12×0.25	7.7	53.0	145.0		32×0.34	13.0	165.0	305.0
14×0.25	8.0	59.0	99.0		36×0.34	13.4	179.0	331.0