

Goldensun Shining Rechargeable LED Flood Light

Picture	Power(W)	Parameter	Carton Measurement (CM)	Color
---------	----------	-----------	----------------------------	-------

Model: JY-RLF-10D1

	10W	Die-casting Aluminium Lamp Body & SMD IP65	12pcs/ctn	White
			51.5*33*40 cm	Warm White
		Size: 240*145*165 mm	0.93 kg/pcs	Red
		Viweing Angle: 120°	13.2 kg/ctn	Yellow
		Data: Luminous Efficiency ≥ 60lm/W		
		Recharger Data: AC110~240V DC8.4V~1000mA		
		Light Up Time: 4H Recharged Time: 3H		
		Battery Capacity: 3.7V 2200mAh Genuine Battery		
		Red,Blue Explosion-flashing+2-grade white light (Single USB/Double USB+Reflect Grid)		

Model: JY-RLF-10D3

	10W	Die-casting Aluminium Lamp Body & SMD IP65	12pcs/ctn	White
			51.5*33*40 cm	Warm White
		Size: 240*145*165 mm	0.93kg/pcs	Red
		Viweing Angle: 120°	13.2kg/ctn	Yellow
		Data: Luminous Efficiency ≥ 60lm/W		
		Recharger Data: AC110~240V DC8.4V~500mA		
		Light Up Time: 4H Recharged Time: 3H		
		Battery Capacity: 7.4V 1500mAh(2AA Battery) Genuine Battery		
		Red,Blue Explosion-flashing+1-grade white light		

Model: JY-RLF-10D1/02

	10W	Die-casting Aluminium Lamp Body & SMD IP65	12pcs/ctn	White
			51.5*33*40cm	Warm White
		Size: 240*145*165 mm	0.93kg/pcs	Red
		Viweing Angle: 120°	13.2kg/ctn	Yellow
		Data: Luminous Efficiency ≥ 60lm/W		
		Recharger Data: AC110~240V DC8.4V~1000mA		
		Light Up Time: 4H Recharged Time: 3H		
		Battery Capacity: 3.7V 2000mAh Genuine Battery		
		Red,Blue Explosion-flashing+3-grade white light		

Model: JY-RLF-20D1

	20W	Die-casting Aluminium Lamp Body	8pcs/ctn	White
		& SMD IP65	47*36*51cm	Warm White
		Size: 270*215*185 mm	1.55kg/pcs	Red
		Viweing Angle: 120°	15.6kg/ctn	Yellow
		Data: Luminous Efficiency $\geq 60\text{lm/W}$		
		Recharger Data: AC110~240V DC8.4V~1000mA		
		Light Up Time: 4H Recharged Time: 4H		
		Battery Capacity: 7.4V 2200mAh(4AA Battery) Genuine Battery		
		Red,Blue Explosion-flashing+1-grade white light		

Model: JY-RLF-20D1-02

	20W	Die-casting Aluminium Lamp Body	8pcs/ctn	White
		& SMD IP65	47*36*51cm	Warm White
		Size: 270*215*185 mm	1.55kg/pcs	Red
		Viweing Angle: 120°	15.6kg/ctn	Yellow
		Data: Luminous Efficiency $\geq 60\text{lm/W}$		
		Recharger Data: AC110~240V DC8.4V~1000mA		
		Light Up Time: 4H Recharged Time: 4H		
		Battery Capacity: 7.4V 4400mAh(4AA Battery) Genuine Battery		
		Red,Blue Explosion-flashing+1-grade white light		