



中国比格科技发展有限公司
CHINA BIG S&T CO., LTD.

ADD: 18F Zhongxin Bank Massion Jiangbei District Chongqing China
Tel: +86-23-67675049 Fax: +86-23-67635036

CKZ6581D3 型公交客车配置表

CKZ6581D3 CITY BUS SPECIFICATIONS

Overall Specification	Over length(mm) 总长	5760	Engine Specification	Engine Model 发动机型号	JX493ZLQ3A (Isuzu tech)
	Over width(mm) 总宽	1910		Engine Type 发动机类型	4 cylinder, in line, vertical, four stroke, forced water cooling, inter-cooling, electronic control common rail 四缸直列, 四冲程, 加强水冷, 中冷, 燃油喷射系统
	Over height(mm) 总高	2350		Displacement(L) 排量	2.771
	Wheelbase(mm) 轴距	3100		Max. output kw/rpm) 最大输出功率	80/3400
	Tread(mm) 轮距	1630/1460		Max.torque(N.M/ rpm) 最大扭矩	260/2000
	Overhang F/R(mm) 悬挂	1195/1465		Fuel Type 燃油类型	Diesel
	Approach/Departure Angle (°) 接近角/离去角	20/14		百公里油耗 Fuel consumption(L/100km)	12
Performanc	Chassis Model 底盘型号	EQ6552	Max. grade ability(%) 最大爬坡度	≥30	
	Engine Position	Front-position	Min. turning	≤16	



中国比格科技发展有限公司
CHINA BIG S&T CO., LTD.

ADD: 18F Zhongxin Bank Massion Jiangbei District Chongqing China
Tel: +86-23-67675049 Fax: +86-23-67635036

	发动机位置	前置	diameter(m) 最小转弯直径	
	Max. speed(km/h) 最大速度	≥100	Fuel Tank Capacity(L) 油箱容积	60
	Brake distance (v=30km/h) 制动距离	≤10	Luggage Compartment(m3) 行李舱容积	0.4
	Curb Weight(kg) 整备质量	2800	Max. total mass(kg) 最大总质量	4700
	Item 条目	Standard Equipment 标配		Optional Equipment 选配
Chassis	Clutch 离合器	Single Dry Plate, Diaphragm spring 单片干式膜片弹簧		
	Transmission 变速箱	5 speed, Soft shaft control, Germany Getrag 5挡, 软轴操控, 品牌德国格特拉克		
	Rear Axle 后桥	3T rear axle, one grade main reducer, 3T 后桥, 单级主减		
	Front Axle 前桥	2T front axle 2T 前桥		
	Frame 车架	Trough model, Riveted joint frame 槽形纵梁, 铆接车架		
	Suspension 悬挂	Less Leaf Spring, telescopic shock absorber, F/R stabilizer bar 少片簧, 伸缩式减振器, 前后稳定杆		
	Steering System 转向系统	Cycling ball type mechanical steering system, adjustable direction lever 循环球式机械转向系统, 可调式方向杆		
	Brake System 制动系统	hydraulic vacuum brake 液压真空制动		
	Tire 轮胎	6.5-15-10, longitudinal water ripple, 5J rim, 6.5-15-10, 纵向水波纹, 5J 轮辋		
	Wiring 线路	12V, Single Wire, Minus Earth 12V, 单线制, 负极搭铁		



中国比格科技发展有限公司
CHINA BIG S&T CO., LTD.

ADD: 18F Zhongxin Bank Massion Jiangbei District Chongqing China
Tel: +86-23-67675049 Fax: +86-23-67635036

	Battery 电池	6-Q-80AH / standard generator 6-Q-80AH/标准型发电机	
	Starter/generator 起动机/发电机	Standard 标准配置	
	Others 其他	整车防腐防锈加强, 密封件加强 Anti-corrosion and seal parts strengthened for the whole vehicle	
Interior Trimming	Body Structure 车身结构	Non-load bearing thin sheel body 非承载式薄壳车身	
	Interior Trimming 内饰	Injection molding instrument console and driver door interior trimming, composite side wall decorative sheet, shaped roof trimming 注塑成型仪表台, 注塑成型驾门内装饰板, 复合侧墙装饰板, 成型顶内饰	
	Door and Door Pump 门和泵	Front driver door on each side, Manual folding passenger door(folded to front), rear luggage cabin door 左、右驾驶门, 电动升降驾窗玻璃, 电子驾门锁, 手动折叠乘客铁门(向前折叠), 后备箱门	
	Windows 窗户	Sliding Passenger window, Front laminated windscreen , rear cemented windscreen 推拉式乘客侧窗, 前夹胶挡风玻璃, 后钢化挡风玻璃	
	Floor 地板	Plastic board with durable floor leather for passenger area, step covered with durable floor leather, shaped floor leather for driving area, injection molding shaped driver door step 乘客区塑料地板加耐磨地板革, 踏步箱耐磨式地板革, 驾驶区一体成型式地板革, 吹塑成型驾区踏步	
	Seat 座椅	16+1+1 seat, 2+1 seat layout, adjustable driver seat, co-driver seat, 3-point safety belt for driver and co-driver seat 16+1+1 座椅, 2+1 布局, 可调式驾驶座椅和	



中国比格科技发展有限公司
CHINA BIG S&T CO., LTD.

ADD: 18F Zhongxin Bank Massion Jiangbei District Chongqing China
Tel: +86-23-67675049 Fax: +86-23-67635036

	副驾驶座椅配备三点式安全带。	
A/C System 空调系统	Separate built-in AC (7500cal/h) 非独立内置式 7500kcal/h	
Handrail and Rings 扶手和吊环	Standard 标准	
Audio&Visual System 视听系统	MP3 播放器	
Rearview System 后视系统	Manual rear view mirror, inner rear view mirror 手动后视镜, 内视镜	
Lamp 灯具	Combined head and Tail Lamp, front and rear fog light, ceiling light, step light 整体式前大灯和尾灯, 前后雾灯, 顶灯, 踏步灯	
Wiper 雨刷	Two speed Rain Wiper 2 挡式雨刷	
Service Facilities 服务设施	Fire Extinguisher, one advertising frame installed at each side of roof. 灭火器, 车顶左右一侧各设置一个广告框	
Paint 漆艺	Polyester paint 聚酯漆	
Memo 备注		