#### Huizhou Yinghua Electronic Co.,Ltd

Established in 2001, Huizhou Yinghua Electronic Co., LTD is a professional manufacturer and solution provider of high-quality automatic voltage stabilizer ranging from 500VA to 60KVA, solar integrated inverters and UPS ranging from 500VA to 10KVA, solar power system ranging from 300W to 5000W, transformers and converters, with brand name of "Powerhero" and "Ipower".

#### Why us?

- 1. We have been a pioneer of technology in CN.We explored the key technology of aluminum transformer production and became the first aluminum transformer supplier.
- 2. ISO & CE certified.
- 3. 10+ years of OEM experience.
- 4. A mighty R&D team.
- 5. Over 200 well-trained workers.
- 6. Customized products to meet different clients' need and various products.
- 7. Complete range of high-quality products including AVR/Inverter/UPS/Solar Inverter/Transformer.
- 8. 19,000  $\text{m}^2$  factory with well-equipped facilities to produce better products.

## **Factory Photo**



# Air-conditioner Automatic Voltage Regulator

## **More Definite Usage & Most Economical**







### **Product Description**

With WA-series stabilizerr can best protect your appliance from voltage fluctuation, ensure your appliance giving its best performance.

#### **Product Feature**

- ---Specific design for definite air conditioner usage, most economical;
- ---Independent SMT processing technology;
- ---Authentic zero-crossing technology
- --- Taylor-made C.R.G.O. toroidal transformer
- ---High performance and high speed MCU control

--Wide input voltage range 140Vac~260Vac/100Vac~260Vac/80Vac~260Vac optional

Series	WSAB 140V-260V	WSAB-1P	WSAB-1.5P	/	WSAB-2P	/	/	WSAB-3P	/
	WTAB 100v-260v~	WTAB-1P	WTAB-1.5P	/	/	WTAB-2P	/	/	WTAB-3P
	WUAB 80v-260v~	WUAB-1P	/	WUAB-1.5P	/	/	WUAB-2P	/	WUAB-3P
Output Power		750W	1150W		1500W			2300W	
Phase		Single							
Transformer		C.R.G.O. toroidal transformer							
Indicator		LED graphic							
Display Status		normal working / time delay / overheat / unusual / over load / over voltage / under voltage							
Output	Frequency	50/60 Hz							
	Voltage	110/120/220/230/240 Vac optional							
	Precision	±10%							
Protection		overload, high temperature, high/low voltage, short circuit							
Delay Function		6 seconds							
Efficiency		98%							
Cooling System		smart cooling							
Environmental	Operating Temperature	0 - 40 ℃							
	Relative Humidity	10%~102% RH, non-condensing							
	Storage Temperature	- 15 - 45 ℃							
Appearance	Size (Max. mm)	230x	225x125	260x275x149.5	230x225x125	260x275x149.	311x311x168	260x275x149.5	311x311x168
	N.W. (kg) WSAB	4.22	4.76	/	5.32	1	1	9.50	/
	N.W. (kg) WTAB	5.34	6.06	/	1	8.00	1	1	11.10
	N.W. (kg) WUAB	6.16	/	8.70	1	1	10.80	1	11.80
Packing	Qty/Ctn		4	2	4	2	1	2	1
	Carton Size (mm)	606x	572x207	666x327x233	606x572x207	666x327x233	386x382x250	666x327x233	386x382x250
	Carton G.W. (kg) WSAB	18.88	21.04	/	23.28	/	/	20.60	/
	Carton G.W. (kg) WTAB	23.36	26.24	/	/	17.60	1	1	12.10
	Carton G.W. (kg) WUAB	26.64	/	19.00	/	/	11.80	/	12.80

# **Payment**

30% T/T in advance, 70% before shipment. Sample in 100% T/T.

# Warranty

#### 12 months

#### **After-sales service**

Each order has 3 engineers to provide technical support.

And one customer service representative to follow up the order.

Must response within 12 hours

#### Note:

For more informations, please contact info@gdyhdz.com