

STAGE BACKGROUND LED CURTAIN SERIES

Module No,	BH-M12.5-3264
Brightness	>1200nits
Pixel pitch	12.5mm
Dot matrix per panel	32*64
Dot pixels per panel	2048
Dimension	W400*L800
Panel area	0.32m ²
Aspect ratio	1:2
Panel weight	4.5kg
Transparency	10%
Pixel type and configuration	SMD3528
Protection level	IP43
Dot pixels per sqm	6400
Operating temperature range	-30° C~60° C
Viewing angle	110°/110°+_5°(Vert/Horz.)
Color temperature	6500K
Contrast ratio	1000:1
Panel material	Aluminum
Drive mode	1/4 Scan
Minimum viewing distance	10m
Color depth	16bit
Grey scale (liner) levels	64k levels per color
Refresh rate	1920Hz
System type	Computer synchronous
Computer video frame rate	50/60Hz
Power consumption	Max.400W per square meter
Input voltage	AC 90~260V
Input power frequency	50~60Hz
Lifetime(50% brightness)	>80000 hours
Mounting system	Rear hanging , fix installation

SHENZHEN **BORCCO** TECHNOLOGY CO., LTD.

No.15 ChaoYang RD, Bldg 3, 4/F, BYF Science and Technology Park, Yanchuan, Songgang, Baoan, Shenzhen, China 518105

TEL: +86 755 33238588

FAX: +86 755 33234370

WEB: www.borcco.com