


2-PC BALL VALVE, FULL BORE, THREADED END, 1000WOG, DIN SIZE:1/4"-4"

- Investment Castings For Body And Cap
- Internal Entry Blow-Out Proof Stem
- Length: DIN 3203-M3
- Pressure Rating: 1000PSI (PN63)
- Threaded Ends: ANSI B2.1, BS 21, DIN 259/2999
- Material: CF8M, CF8, CF3M, WCB
- Pressure Test : API 598



MATERIAL LIST

ITEM	PART	MATERIAL	QTY
1	BODY	CF8M	1
2	BALL SEAT	R-PTFE	2
3	BALL	CF8M	1
4	BODY GASKET	PTFE	1
5	CAP	CF8M	1
6	STEM	SS316	1
7	THRUST WASHER	PTFE	1
8	STEM PACKING	PTFE	1
9	GLAND NUT	SS304	1
10	HANDLE	SS304	1
11	SPRING WASHER	SS304	1
12	NUT	SS304	1
13	LOCK DEVICE	SS304	1
14	HANDLE COVER	PLASTIC	1

DIMENSION TABLE

SIZE	d	L	H	W	N.M	KGS
1/4"	6	50	50	100	4	0.22
3/8"	10	60	50	100	4	0.20
1/2"	15	75	52	100	5	0.34
3/4"	20	80	57	115	8	0.52
1"	25	90	78	150	10	0.78
1-1/4"	32	110	88	150	14	1.23
1-1/2"	40	120	95	180	18	2.00
2"	50	140	100	180	25	2.98
2-1/2"	65	185	120	245	48	6.05
3"	80	205	130	245	75	9.90
4"	100	240	160	278	110	16.60

