



Fleece Tape

(N105 095 02)

Function: It is specialized used for wrapping automotive wire harness, This product is adopt good radix material, have strong superficial anti-dirty ability and high temperature resistance stability, suitable for internal delicate position of auto. With features of easy unwinding, vibration proof, sound reducing, good adhesion and tensile strength. Used for auto wire harness wrapping.

Technical Data

| | Dimension | Values | Test Method |
|---------------------|-----------|----------|-------------|
| Thickness | mm | 0.3±0.05 | Vw60360 |
| Width | mm | 19 | Vw60360 |
| Adhesion Strength | N/cm | 4.3 | Vw60360 |
| Tensile Strength | N/cm | 60 | Vw60360 |
| Elongation | % | 35 | Vw60360 |
| Temperature Range | ℃ | -40/105 | Vw60360 |
| Abrasion resistance | | 127 | Vw60360 |
| unwind strength | N | 5.6 | Vw60360 |
| Tear by hand | | YES | Vw60360 |
| Flame stability | Mm/min | 63 | Vw60360 |
| Noise reduction | dB | 6 | Vw60360 |

Gule : Pressure sensitive adhesive

colour: black

structure: high quality rubber velvet adhesive tape, strong anti-aging ability

Certificate: ▶ company system: TS16949

▶ Product test reports: SGS, OTS approval by China FAW-VW, CTI

Advantages:

- 1) High adhesive force
- 2) Tearable by hand
- 3) Very big resistance against abrasion
- 4) Flexible and easy to handle