

山东瑞泰玻璃绝缘子有限公司
SHANDONG RUITAI GLASS INSULATOR CO.,LTD

ADD.:NO.508 LIANHUASHAN ROAD,XINTAI CITY,
SHANDONG PROVINCE,P.R.CHINA
PHONE:+86 538 6378887 FAX:+86 538 6378883

INSULATOR TECHNICAL DATA SHEET



| | | |
|--|---|---------|
| Manufacturer | SHANDONG RUITAI GLASS INSULATOR CO.,LTD | |
| Type | U70BL | |
| Material | Toughened Glass | |
| Standards | IEC | |
| Spacing(P) | mm | 146 |
| Diameter of shell | mm | 255 |
| Creepage distance | mm | 320 |
| Ball and socket coupling | 16 | |
| Power frequency | | |
| Dry withstand voltage | kv | 70 |
| Wet withstand voltage | kv | 40 |
| Lightning impulse withstand voltage | kv | 100 |
| Power frequency puncture voltage | kv | 130 |
| Radio influence voltage | μ V | 50 |
| Electric iron visual test | kv | 18/22 |
| Impulse overvoltage puncture withstand voltage | 2.8 | |
| kv | | |
| Power frequency electric arc test | s/kA | 0.12/20 |
| Net weight per unit | kg | 3.6 |