

## Anti-explosion Camera (CW-669)

Image Device	1/3" SONY EXview HAD CCD II	
TV System	PAL	NTSC
Effective Pixels	976(H)*582(V)	976(H)*494(V)
Sensing Area	5.58mmx4.67mm	
Scanning System	2:1 Interlace	
Sync. System	Internal	
Resolution	700TV Lines	
WDR	YES	
ATR	YES	
2D noise reduction	YES	
Digital demist process	YES	
Privacy mask	YES	
Face detection	YES	
Motion detection	YES	
HLR(high light reduction )	YES	
OSD	supports 8 Languages	
Horizontal Sync Frequency	15.625 kHz	15.734 kHz
Vertical Sync Frequency	50 Hz	60 Hz
Video Output	1.0Vp-p, 75Ohm	
Gamma Consumption	0.45	
AGC	Auto	
S/N Ratio	Better than 48dB	
White Balance	Auto	
Electronic Shutter	1/60(NTSC)/1/50(PAL)~1/100,000 Seconds	
BLC	Auto	
Storage Temperature	-50°C ~ 95°C, RH95%MAX.	
Operating Temperature	-30°C~85°C	
Minimum Illumination	0 Lux	
Power Supply	DC12V	
Night vision distance	8~10m	
Anti-hazard classification	Exd II CT6	
Waterproof rating	IP69K	
Image mode	Normal	
Viewing Angle	□120°	□92° □69°
Material quality	304 Stainless steel	



广州敏视数码科技有限公司

Sharpvision Co., Ltd

Tel.: +86 20 6667 0988 Fax.: +86 20 6667 0977

Email: sales@sharpvision.cn MSN: sales@sharpvision.cn Skype: sharpvision8

Address: 1/F., #6 Building, Huangzhou Industrial Park, Chebei Rd., Tianhe, 510660 Guangzhou, China.



For Safer Driving