




















		Max SWL=Mode Coefficient P*working Load Limit						Max SWL of lifting method								
Code	Color	Single Max Working Load Limit						2-Legs Max Working Load Limit				Approx width (mm)			min length (m)	max length (m)
		Upright	Choked					Upright	Choked	Upright	Choked					
				0°-7°	7°-45°	45°-60°	45°					5:1	6:1	7:1		
EB-A-01		1000	800	2000	1400	1000	700	1400	1120	1000	800	25	25	30	1	100
EB-A-02		2000	1600	4000	2800	2000	1400	2800	2240	2000	1600	50	50	60	1	100
EB-A-03		3000	2400	6000	4200	3000	2100	4200	3360	3000	2400	75	75	90	1	100
EB-A-04		4000	3200	8000	5600	4000	2800	5600	4480	4000	3200	100	100	120	1	100
EB-A-05		5000	4000	10000	7000	5000	3500	7000	5600	5000	4000	125	125	150	1	100
EB-A-06		6000	4800	12000	8400	6000	4200	8400	6720	6000	4800	150	150	180	1	100
EB-A-08		8000	6400	16000	11200	8000	5600	11200	8960	8000	6400	200	200	240	1	100
EB-A-10		10000	8000	20000	14000	10000	7000	14000	11200	10000	8000	250	250	300	1	100
EB-A-12		12000	9600	24000	16800	12000	8400	16800	13440	12000	9600	300	300	300	3	100
EB-A-15		15000	12000	40000	28000	15000	14000	28000	22400	15000	12000	200	200	240	3	100
EB-A-20		20000	16000	60000	42000	20000	21000	42000	33600	20000	16000	250	250	300	3	100
EB-A-25		25000	20000	50000	35000	25000	17500	35000	28000	25000	20000	300	300	300	3	100
EB-A-30		30000	24000	60000	42000	30000	21000	42000	33600	30000	24000	300	300	300	3	100
EB-A-40		40000	32000	80000	56000	40000	28000	56000	44800	40000	32000				3	100
EB-A-50		50000	40000	100000	70000	50000	35000	70000	56000	50000	40000				3	100

